



**marathon™**  
Special Products

Product Data Sheet

**132X670**

Replace "x" with 1, 2, or 3 for number of poles

Power Terminal Block

## 175 Amps 600 Volts AC/DC

### Wire Range

- Line: (1) 2/0 - #14 AWG
- Load: (4) 4 - #14 AWG + (1) 1/4" Quick-connect tab (20 amps)

### Electrical Ratings

- 175 Amps
- 600V per UL 1059 & CSA 22.2 No.158, class B & C requirements
- SCCR of 10,000 A (default for terminal blocks).
- CU9AL - 90°C connector terminal rating with copper or aluminum wire
- Factory & Field Wiring

### Agency Compliance

- UR - UL Recognized Terminal Block, Evaluated to UL 1059, File No.XCFR2.E62806
- CSA - certified to C22.2 No. 158, File No. LR19766 (wire classes B & C only)
- CE compliant to IEC 60947-7-1


### Material Information

- Insulator base:
  - Thermoplastic
  - Flammability rating of insulator base UL94V0
  - Insulator base temperature rating: -40°C to 125°C (UL RTI)
- Connector: copper, tin plated
- Terminal screws: steel, nickel plated
- Connector mounting screws: steel, zinc plated
- RoHS compliant


A Regal Brand

**REGAL**

## Termination Specifications

Line Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	2/0 - 1/0	13.6 N·m (120 lbf·in)	1	B, C
	1 - 6	13.6 N·m (120 lbf·in)	1	B, C, G, H, I (DLO)
	8	4.5 N·m (40 lbf·in)	1	B, C, G, H, I (DLO)
	10 - 14	4 N·m (35 lbf·in)	1	B, C, I (DLO)

- Solid copper wire range: 10 - 14 AWG
- Wire strip length: 3/4 in. (19mm)
- Terminal screw drive: 5/16 in. hex

Load Side	Wire Size (CU Stranded)	Torque	Wires / Terminal	Wire Class (UL) <sup>1</sup>
	4	4 N·m (35 lbf·in)	1	B, C
	6 - 8	4 N·m (35 lbf·in)	1	B, C, G, H, I (DLO)
	10	4 N·m (35 lbf·in)	1 - 2	B, C, I (DLO)
	12 - 14	4 N·m (35 lbf·in)	1 - 4	B, C
1 - 2			I (DLO)	

- Solid copper wire range: 10 - 14 AWG
- Wire strip length:
  - top row: 7/16 in. (11mm)
  - bottom row: 11/16 in. (17mm)
- Terminal screw drive: slotted

<sup>1</sup> For information on copper stranded wire classes please visit:  
<http://www.marathonsp.com/flexible-stranded-wire.php>

## Installation & Accessories

- Mounting (Panel or Din):
  - For use with #10 fastener.
  - Torque mounting fastener to 25-30 lbf-in (2.8 - 3.4 N·m).
  - 7.5 X 35 mm din rail mountable
- Covers:
  - Snap on, hinge covers available upon request
  - Catalog Number: CC132x (replace "x" with number of poles)
  - Covers are black thermoplastic
  - Accessory covers are not intended to provide insulation for electrical spacings.
- Insulator base adders and 1 pole product can be snapped together through integral dovetails to create variable pole power blocks
- Marker Strip: white vinyl strip with mounting screws available.
- Printing options available, consult customer service for specifications
- End bracket for din rail mounting: MSK35

## Drawing

