



bulgin
a brand of Elektron Technology



Shortform Catalogue 2014



A full range of dust and waterproof circular connectors with ratings from IP66, IP68 to IP69K designed to provide safe and secure connections in harsh or hostile conditions. Including the EXPLORA ATEX Zone 2 approved Hazardous Area range of connectors. The Power Buccaneer range consists of the miniature 400 Series, Mini, Standard, 900 series and the new 6000 and 7000 series Buccaneer.

The 6000 series has a unique push-pull latching mechanism with locking facility, the 7000 series has a rapid twist locking system, both ranges are available in interchangeable metal and plastic body versions.

Each range has flex cable connector, in-line flex cable connector and panel mounting connector options. With a wide choice of alternatives from 2 to 25 poles, BNC connections and screw, solder or crimp Terminations.

The Data Buccaneer range includes designs for Ethernet, USB, Mini USB, SMB interfaces. Ethernet Buccaneer meets Cat 5e requirements for data rates up to 100Mbps, USB and Mini USB Buccaneer meets USB version 2.0 specification for data rates up to 480Mbps, SMB Buccaneer has a frequency response up to 4GHz, and for wireless applications there's the SMB waterproof antenna. The Buccaneer range provides the answer to many 'real-world' design problems.

6000 Series Buccaneer - Power



<p>PXP6010</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Flex Cable Connector Mates with all other body styles 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) 4-10mm cable acceptance Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>	<p>PXP6011</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling In-line Flex Cable Connector Mates with PXP6010 & PXM6010 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) 4-10mm cable acceptance Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>	<p>PXP6012</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Panel mount Connector Mates with PXP6010 & PXM6010 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>
<p>PXM6010</p>	<ul style="list-style-type: none"> Metal version Push/pull coupling Flex Cable Connector Mates with all other body styles 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) 4-10mm cable acceptance Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>	<p>PXM6011</p>	<ul style="list-style-type: none"> Metal version Push/pull coupling In-line Flex Cable Connector Mates with PXP6010 & PXM6010 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) 4-10mm cable acceptance Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>	<p>PXM6012</p>	<ul style="list-style-type: none"> Metal version Push/pull coupling Panel mount Connector Mates with PXP6010 & PXM6010 2, 3, 8, 16 & 22 pole Plug or Socket 16A, 277 V (max) Overall diameter 32mm <p>CSA, UL, VDE approvals pending</p>

6000 Series Buccaneer - Ethernet



<p>PXP6034</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Re-wireable flex Cable Connector Mates with panel mounting connectors (PXP6033TP) Two versions: for PE and PUR jacket cable Supplied with shielded RJ45 <p>UL approvals pending</p>	<p>PXP6033TP</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Front Panel Mounting Connector Sealed through panel Mates with PXP6037, PXP6038, PXP6034 flex connectors Cat 5e shielded coupler Standard patchcord can be plugged into rear Version with earth wire available UL approvals pending 	<p>PXP6037</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Overmoulded construction Mates with panel mounting connectors (PXP6033TP) Single or double ended Standard lengths: 2m, 3m & 5m PUR jacket cable S-FTP cable construction Exceeds EIA/TIA Cat 5e UL approvals pending
<p>PXM6034</p>	<ul style="list-style-type: none"> Metal version Push/pull coupling Re-wireable flex Cable Connector Mates with panel mounting connectors (PXP6033TP) Two versions: for PE and PUR jacket cable Supplied with shielded RJ45 <p>UL approvals pending</p>	<p>PXM6033TP</p>	<ul style="list-style-type: none"> Metal version Push/pull coupling Front Panel Mounting Connector Sealed through panel Mates with PXP6037, PXP6038, PXP6034 flex connectors Cat 5e shielded coupler Standard patchcord can be plugged into rear Version with earth wire available UL approvals pending 	<p>ACCESSORIES</p>	<ul style="list-style-type: none"> Metal & Plastic versions Push/pull coupling Sealing caps: For flex connectors For panel mounting connectors Maintain sealing integrity <p>UL approvals pending</p>

6000 Series Buccaneer - USB



<p>PXP6040 / 41</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Single and double ended sealed cable assembly 'A' type and 'B' type USB connector interfaces Mates with all panel mounting styles Available in 2m, 3m and 5m lengths 	<p>PXP6042</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Front Panel Mounting Connector PX06042/A - USB 'A' type sealed connector PX06042/B - USB 'B' type sealed connector Opposite connector to rear of panel Mates with PXP6040 and PXP6041 cable connectors 	<p>PXP6043</p>	<ul style="list-style-type: none"> Plastic version Push/pull coupling Front Panel Mounting Connector PX6043/A - USB 'A' type sealed connector PX06043/B - USB 'B' type sealed connector Leaded with 5 way crimp connector Mates with PXP6040 and PXP6041 cable connectors
----------------------------	--	-----------------------	---	-----------------------	--






7000 Series Buccaneer



<p>PXP7010</p>	<ul style="list-style-type: none"> Plastic version Rapid twist locking Flex Cable Connector Mates with all other body styles 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) 5-15mm cable acceptance Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>	<p>PXP7011</p>	<ul style="list-style-type: none"> Plastic version Rapid twist locking In-line Flex Cable Connector Mates with PXP7010 & PXM7010 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) 5-15mm cable acceptance Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>	<p>PXP7012</p>	<ul style="list-style-type: none"> Plastic version Rapid twist locking Panel mount Connector Mates with PXP7010 & PXM7010 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>
<p>PXM7010</p>	<ul style="list-style-type: none"> Metal version Rapid twist locking Flex Cable Connector Mates with all other body styles 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) 5-15mm cable acceptance Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>	<p>PXM7011</p>	<ul style="list-style-type: none"> Metal version Rapid twist locking In-line Flex Cable Connector Mates with PXP7010 & PXM7010 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) 5-15mm cable acceptance Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>	<p>PXM7012</p>	<ul style="list-style-type: none"> Metal version Rapid twist locking Panel mount Connector Mates with PXP7010 & PXM7010 2, 3, 6, 10 & 32 pole Plug or Socket 25A, 600 V (max) Overall diameter 42mm <p>CSA, UL, VDE approvals pending</p>

EXPlora ATEX Zone 2 Certified



 <p>EXP-0911</p>	<ul style="list-style-type: none"> Quick start thread coupling ATEX Zone 2 Certified Mates with EXP-0921, EXP-A921, EXP-0931 & EXP-0941 Plug or socket versions 7-13mm dia cable acceptance - EXP-0 14-22mm dia cable acceptance - EXP-A Strain Relief Clamp - EXP-A series Up to 18A, 600V ac/dc rating 2, 3, 4, 5, 7 and 10 pole 	 <p>EXP-A921</p>	<ul style="list-style-type: none"> Quick start thread coupling ATEX Zone 2 Certified Mates with EXP-0911, EXP-A911 Plug or socket versions 7-13mm dia cable acceptance - EXP-0 14 - 22mm dia cable acceptance - EXP-A Strain Relief Clamp - EXP-A series Up to 18A, 600V ac/dc rating 2, 3, 4, 5, 7 and 10 pole 	 <p>EXP-0931</p>	<ul style="list-style-type: none"> Quick start thread coupling ATEX Zone 2 Certified Panel mount connector Mates with EXP-0911, EXP-A911 Plug or socket versions Up to 18A, 600V ac/dc rating 2, 3, 4, 5, 7 and 10 pole
 <p>EXP-0941</p>	<ul style="list-style-type: none"> Quick start thread coupling ATEX Zone 2 Certified Flange mount connector Mates with EXP-0911, EXP-A911 Plug or socket versions Up to 18A, 600V ac/dc rating 2, 3, 4, 5, 7 and 10 pole 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Quick start thread coupling Heavy duty sealing caps to maintain IP68 rating of unmated connectors, with stainless steel straps 		
















900 Series Buccaneer



 <p>PX0911</p>	<ul style="list-style-type: none"> Quick start thread coupling Flex Cable Connector Mates with all other styles 2, 3, 4, 5, 7 & 10 pole Plug or Socket 32A, 600 V (7 pole 430V) 7-15mm cable acceptance Overall diameter 58mm 	 <p>PXA921</p>	<ul style="list-style-type: none"> Quick start thread coupling In-Line Flex Cable Connector Mates with PX0911 & PXA911 2, 3, 4, 5, 7 & 10 pole Plug or Socket 32A, 600V (7 pole 430V) 14-22mm cable acceptance Strain relief clamp 	 <p>PX0931</p>	<ul style="list-style-type: none"> Quick start thread coupling Panel Mount Connector Anti-rotation key 2, 3, 4, 5, 7 & 10 pole Mates with PX0911 & PXA911 Plug or Socket 32A, 600V (7 pole 430V) 3-7mm panel thickness 
 <p>PX0941</p>	<ul style="list-style-type: none"> Quick start thread coupling Flange Mount Connector 2, 3, 4, 5, 7 & 10 pole Mates with PX0911 & PXA911 Plug or Socket 32A, 600V (7 pole 430V) 6.2mm dia mounting holes 	 <p>PX0950</p>	<ul style="list-style-type: none"> Quick start thread coupling Additional Bulkhead Adaptor For use with PX0941 to give a 45° or 90° angle 6.2mm dia mounting holes 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Quick start thread coupling Sealing caps to maintain IP68 rating of unmated connectors PX0990 Heavy duty sealing cap for use with PX0911 and PXA911 PX0991 Heavy duty sealing cap for use with PX0921 and PXA921 PX0992 Heavy duty sealing cap for use with PX0931 and PX0941











Standard Buccaneer



 <p>FLEX CABLE CONNECTOR</p>	<ul style="list-style-type: none"> Screw coupling Flex Cable Connector Mates with in-line flex connector and all panel connectors Poles 2, 3, 4, 6, 7, 9, 12, 25 or BNC Plug or Socket 1-12 Amp, 50-250V ac/dc 3.5-9mm cable acceptance Overall diameter 38mm 	 <p>OVERMOULDED CONNECTORS</p>	<ul style="list-style-type: none"> Screw coupling Overmoulded cable assemblies Up to 14mm dia cable with PVC or PU jackets PX0700 flex cable connector Mates with in-line flex connector and all panel connectors 	 <p>IN-LINE FLEX CABLE CONNECTOR</p>	<ul style="list-style-type: none"> Screw coupling In-Line Flex Mounting Connector Mates with Flex Mounting Connector Poles 2, 3, 4, 6, 7, 9, 12, 25 or BNC Plug or Socket 1-12 Amp, 50-250V ac/dc 3.5-9mm cable acceptance 
 <p>PANEL CONNECTOR</p>	<ul style="list-style-type: none"> Screw coupling Front Panel Mounting Connector Mates with Flex Cable Connector Poles 2, 3, 4, 6, 7, 9, 12, 25 or BNC Plug or Socket 1-12 Amp, 50-250V ac/dc 	 <p>REAR PANEL MOUNT CONNECTOR</p>	<ul style="list-style-type: none"> Screw coupling Rear of Panel Mounting Connector PC Spills or screw terminals Mates with Flex Cable Connector Poles 2, 3, 6, 9, 12, 25 Plug or Socket 1-12 Amp, 50-250V ac/dc 	 <p>LOW PROFILE FLANGE MOUNTING</p>	<ul style="list-style-type: none"> Screw coupling Low Profile Flange Mounting Connector Mates with Flex Cable Connector Poles 2, 3, 4, 6, 7, 9, 12, 25 or BNC Plug or Socket 1-12 Amp, 50-250V ac/dc 
 <p>BULKHEAD/SURFACE MOUNTING</p>	<ul style="list-style-type: none"> Screw coupling Bulkhead/Surface Mounting Connector Mates with Flex Cable Connector Poles 2, 3, 4, 6, 7, 9, 12, 25 or BNC Plug or Socket 1-12 Amp, 50-250V ac/dc 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Screw coupling Sealing caps to maintain IP68 rating of unmated connectors PX0734 fits Flex Mounting Connector PX0733 fits In-Line Flex, Front Panel Mount, Flange Mount and Bulkhead connectors PX0711 for PCB and Rear Panel Mount connectors 	 <p>INLINE CONNECTOR</p>	<ul style="list-style-type: none"> Screw coupling IP68 Rated In-Line Connector Standard Cable Acceptance 6-8mm Cable Range 3.5-9mm (using alternative glands) Supplied with 3 way Terminal Block Available Moulded in Black or Orange Also available with Ethernet RJ45 connections

Mini Buccaneer



 <p>PX0800 - shown with insert</p>	<ul style="list-style-type: none"> Screw coupling Flex Cable Connector Mates with Flex In-Line or Panel Mounting versions Suitable for Pin, Socket or BNC inserts Cable acceptance 3.5-9mm (Standard 5-7mm) Overall diameter 26mm 	 <p>PX0802 - shown with insert</p>	<ul style="list-style-type: none"> Screw coupling Panel Mounting Connector Mates with PX0800 Single hole fixing Suitable for Pin, Socket or BNC inserts 	 <p>PX0805 - shown with insert</p>	<ul style="list-style-type: none"> Screw coupling Panel Mounting Connectors Mates with PX0800 Suitable for Pin, Socket or BNC inserts PX0804 as PX0805 but without sealing cap retaining clip 
 <p>PX0801 - shown with insert</p>	<ul style="list-style-type: none"> Screw coupling In-Line Flex Cable Connector Mates with PX0800 Suitable for Pin, Socket or BNC inserts Cable acceptance 3.5-9mm (Standard 5-7mm) 	 <p>SCREW TERMINAL INSERTS</p>	<ul style="list-style-type: none"> Screw coupling 2, 3, 4 and 6 poles 3-10A, 250V ac Fits all body styles Leading earth pin on 3, 4 and 6 pole inserts 	 <p>SOLDER/CRIMP INSERTS</p>	<ul style="list-style-type: none"> Screw coupling For solder or crimp contacts 5A, 380V ac 3 or 8 pin Fits all body styles




400 Series Buccaneer



 <p>PX0410/P PX0410/S</p>	<ul style="list-style-type: none"> Screw coupling Flex Cable Connector Mates with PX0401, PX0411, PX0412 and PX0413 2, 3, 4, 6, 8, 10 and 12 pole Pin or Socket inserts 1-8A, 50-250V ac/dc Cable acceptance 3-7mm Overall diameter 19mm 	 <p>PX0411/P PX0411/S</p>	<ul style="list-style-type: none"> Screw coupling In-line Flex Cable Connector Mates with PX0410 & PX0400 2, 3, 4, 6, 8, 10 and 12 pole Pin or Socket inserts 1-8A, 50-250V ac/dc Cable acceptance 3-7mm Overall diameter 19mm 	 <p>PX0401, PX0400</p>	<ul style="list-style-type: none"> Screw coupling Overmoulded cable assemblies Up to 9mm dia cable with PVC or PU jackets PX0400: Flex cable connector, mates with in-line flex connectors PX0401: In-line flex cable connector, mates with in-line flex connectors and all panel connectors
 <p>PX0412/P PX0412/S</p>	<ul style="list-style-type: none"> Screw coupling Front Panel Mounting Connector Mates with PX0410 2, 3, 4, 6, 8, 10 and 12 pole Pin or Socket inserts 1-8A, 50-250V ac/dc Single hole fixing - 16.1mm dia. D Crimp or solder contacts - supplied separately 	 <p>PX0413</p>	<ul style="list-style-type: none"> Screw coupling Mates with Flex Cable connector PX0410 Rear Panel mounting Single hole fixing - 19.1mm dia. D 2, 3, 4, 6, 8, 10 or 12 pole PX0413: Crimp or solder contacts - supplied separately PX0413/PC: straight PC spills, pre-loaded gold plated contacts 	 <p>PX0480, PX0480/1, PX0481, PX0484</p>	<ul style="list-style-type: none"> Screw coupling Sealing caps to maintain IP68 rating of unmated connectors PX0480/1 - fits PX0411 style PX0480 - fits PX0412 style PX0481 - fits PX0410 style PX0484 - fits PX0413 styles







SMB Buccaneer



 <p>PX0415</p>	<ul style="list-style-type: none"> Screw coupling Flex cable connector Mates with Panel connector (PX0414) PX0415 - Re-wireable connector for RG-174 cable PX0416 - Pre-wired with RG-174 cable Gold plated SMB plug 50WΩ impedance 	 <p>PX0414</p>	<ul style="list-style-type: none"> Screw coupling Front panel mount connector Mates with Flex connectors (PX0415, PX0416) Single hole fixing Supplied with SMB jack terminated with RG-174 cable 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Screw coupling SMB Antenna Dust & waterproof to IP68 EN60529 when mated Built-in sealed antenna Frequency bands: 2.4 to 2.5GHz, 440 to 470MHz, 850-900/1800/1900MHz Mates with SMB Buccaneer PX0414
---	--	---	---	---	--









Mini USB Buccaneer



 <p>PX0444</p>	<ul style="list-style-type: none"> Screw coupling Single ended sealed cable assembly Sealed Mini 'A' to Mini 'B' Fully overmoulded construction Available in 2, 3 & 4.5m lengths Mates with PX0456, PX0457 & PX0458 	 <p>PX0441, PX0442</p>	<ul style="list-style-type: none"> Screw coupling Single ended sealed cable assembly Sealed Mini 'B' to either Standard 'A' or Mini 'A' type Fully overmoulded construction Available in 2, 3 & 4.5m lengths Mates with PX0443, PX0446 & PX0447 	 <p>PX0443, PX0456</p>	<ul style="list-style-type: none"> Screw coupling Mini 'B' type or Mini 'AB' type Front panel mounting connector leaded with 5 way crimp, for use with PC header or rear panel mounting connector with leaded 5 way header Mates with PX0441 & PX0442 type cables
 <p>PX0446, PX0457</p>	<ul style="list-style-type: none"> Screw coupling Mini 'B' or Mini 'AB' type Rear panel mounting connector leaded with 6 way header or front panel mounting connector leaded with 6 way crimp, for use with PC header Mates with PX0441 & PX0442 type cables 	 <p>PX0447, PX0458</p>	<ul style="list-style-type: none"> Screw coupling Mini 'B' type or Mini 'AB' type Rear panel mounting connector PCB mounting Mates with PX0441 & PX0442 type cables 	 <p>PX0480, PX0484 & PX0485</p>	<ul style="list-style-type: none"> Screw coupling Sealing caps to maintain IP68 rating of unmated connectors 5 way headers for use with PX0443 PX0480 - fits PX0443 PX0484 - fits PX0446 & PX0447 PX0485 - fits PX0441 & PX0442

Ethernet Buccaneer



 <p>PX0836, PX0837, PX0838</p>	<ul style="list-style-type: none"> Screw coupling Mates with panel mounting connectors (PX0833, PX0839, PX0870) Single or double ended Standard lengths: 2m, 3m & 5m PUR jacket cable Supplied with shielded RJ45 plug S-FTP cable construction Wiring configuration to 568-B Exceeds EIA/TIA Cat 5e 	 <p>PX0834</p>	<ul style="list-style-type: none"> Screw coupling Flex Cable Connector Mates with panel mounting connectors (PX0833, PX0839, PX0870) Supplied with shielded RJ45 plug Two versions: for PE and PUR jacket cable (Cat 5e) for other cable sizes from 3.5 to 8mm dia 	 <p>PX0833</p>	<ul style="list-style-type: none"> Screw coupling Front Panel Mounting Connector Mates with PX0836, PX0837, PX0839 and PX0834 flex connectors Cat 5e shielded coupler Standard patchcord can be plugged into rear Version with earth wire available Single hole fixing Complete with panel sealing gasket
 <p>PX0839/PC</p>	<ul style="list-style-type: none"> Screw coupling Cat 5e shielded RJ45 interface Rear of panel mounted Mates with PX0836, PX0837, PX0838 and PX0834 flex connectors For direct horizontal mounting to PCB with straight pins or vertical mounting to PCB with 90° pins Complete with panel sealing gasket 	 <p>PX0839/IDC</p>	<ul style="list-style-type: none"> Screw coupling Cat 5e shielded RJ45 interface Rear of panel mounted Mates with PX0836, PX0837, PX0838 and PX0834 flex connectors IDC blocks for discreet termination Complete with panel sealing gasket 	 <p>PX0870</p>	<ul style="list-style-type: none"> Screw coupling Cat 5e shielded RJ45 interface Flange fixing Mates with PX0836, PX0837, PX0838 and PX0834 flex connectors Version with earth wire available Complete with panel sealing gasket
 <p>PX0888</p>	<ul style="list-style-type: none"> Screw coupling Shielding back shell Maintains screening directly to panel Can is fixed to rear of panel mount connector For use on PX0833 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Screw coupling Sealing caps to maintain IP68 rating of unmated connectors PX0835 - fits PX0834, PX0836-PX0838 PX0733 - fits PX0833 PX0711 - fits PX0839 		

USB Buccaneer®























 <p>PX0840/A</p>	<ul style="list-style-type: none"> Screw coupling Single ended sealed cable assembly IP68 'A' type USB connector to standard 'B' type USB connector Mates with all panel mounting styles Available in 2m, 3m and 5m lengths 	 <p>PX0840/B</p>	<ul style="list-style-type: none"> Screw coupling Single ended sealed cable assembly IP68 'B' type USB connector to standard 'A' type USB connector Mates with all panel mounting styles Available in 2m, 3m and 5m lengths 	 <p>PX0841/AB</p>	<ul style="list-style-type: none"> Screw coupling Double ended sealed cable assembly IP68 'A' type USB connector to IP68 'B' type USB connector Mates with all panel mounting styles Available in 2m, 3m and 5m lengths
 <p>PX0842/A PX0842/B</p>	<ul style="list-style-type: none"> Screw coupling Front Panel Mounting Connector PX0842/A - USB 'A' type IP68 connector PX0842/B - USB 'B' type IP68 connector Opposite connector to rear of panel Mates with PX0840 and PX0841 cable connectors 	 <p>PX0843/A PX0843/B</p>	<ul style="list-style-type: none"> Screw coupling Front Panel Mounting Connector PX0843/A - USB 'A' type IP68 connector PX0843/B - USB 'B' type IP68 connector Leaded with 5 way crimp connector Mates with PX0840 and PX0841 cable connectors 	 <p>PX0848/A PX0848/B</p>	<ul style="list-style-type: none"> Screw coupling Rear Panel Mounting Connector PX0848/A - USB 'A' type IP68 connector PX0848/B - USB 'B' type IP68 connector Opposite connector to rear of panel Mates with PX0840 and PX0841 cable connectors
 <p>PX0849/A PX0849/B</p>	<ul style="list-style-type: none"> Screw coupling Rear Panel Mounting Connector PX0849/A - USB 'A' type IP68 connector PX0849/B - USB 'B' type IP68 connector Leaded with 5 way header Mates with PX0840 and PX0841 cable connectors 	 <p>PX0845/A PX0845/B</p>	<ul style="list-style-type: none"> Screw coupling Rear Panel Mounting Connector PX0845/A - USB 'A' type IP68 connector PX0845/B - USB 'B' type IP68 connector PCB contacts at rear Mates with PX0840 and PX0841 cable connectors 	 <p>PCB ADAPTOR LEADS</p>	<ul style="list-style-type: none"> Screw coupling Standard A and B type USB connectors to 5 way, 2.54mm, crimp adaptor leads 5 way headers, 2.54mm pitch, horizontal or vertical mounting For use with PX0842 & PX0848 types
 <p>PX0852</p>	<ul style="list-style-type: none"> Screw coupling For use with USB Flash Drives Maintains IP68 rating when mated For use with 'A' type connectors: PX0842, PX0843, PX0845, PX0848 & PX0849 Internal accommodation 17.5 x 14.0 x 83mm approx. 	 <p>SEALING CAPS</p>	<ul style="list-style-type: none"> Screw coupling Sealing caps to maintain IP68 rating when connectors are not in use PX0835 for cable connectors PX0840 and PX0841 PX0733 for front panel mount connectors PX0842 and PX0843 PX0711 for rear panel mount connectors PX0848, PX0849 and PX0845 		

FILTERS

Designed to reduce conducted mains borne EMI, this extensive range provides many solutions to EMI problems. To meet individual design requirements the

filters are available with one standard filter circuit. Current ratings are from 1 to 10 amps with single or twin fused types also available.

The choice of mounting options will suit most applications with flange, snap to panel or base/bulkhead.

 <p>PS00</p>	<ul style="list-style-type: none"> Flange Mounting 1, 3, 6 or 10 Amp Current Rating 2.8 or 6.3mm tabs 		 <p>PS01</p>	<ul style="list-style-type: none"> Snap Fit for 1, 1.5, 2 or 3mm Panels 1, 3, 6 or 10 Amp Current Rating 2.8 or 6.3mm tabs 	
 <p>PS02</p>	<ul style="list-style-type: none"> Base Mounting 1, 3, 6 or 10 Amp Current Rating 2.8 or 6.3mm tabs 		 <p>PS03</p>	<ul style="list-style-type: none"> Bulkhead Mounting 1, 3, 6 or 10 Amp Current Rating 2.8 or 6.3mm tabs 	
 <p>PS20/A</p>	<ul style="list-style-type: none"> Flange Mounting 1, 3, 6 or 6 Amp Current Rating Fused 2.8 or 6.3mm tabs 		 <p>PS21/A</p>	<ul style="list-style-type: none"> Snap Fit for 1, 1.5, 2 or 3mm Panels 1, 3, 6 or 6 Amp Current Rating Fused 2.8 or 6.3mm tabs 	
 <p>PS22/A</p>	<ul style="list-style-type: none"> Panel Mounting 3 or 6 Amp Current Rating Fused High Performance 2.8 or 6.3mm tabs 		 <p>PS23/A</p>	<ul style="list-style-type: none"> Snap Fit for 1, 1.5, 2 or 3mm Panels 3 or 6 Amp Current Rating Fused High Performance 2.8 or 6.3mm tabs 	
 <p>PS25</p>	<ul style="list-style-type: none"> Flange Mounting 2 or 4 Amp Current Rating Twin Fused 2.8 or 6.3mm tabs 		 <p>PS26</p>	<ul style="list-style-type: none"> Snap Fit for 1, 1.5, 2 or 3mm Panels 2 or 4 Amp Current Rating Twin Fused 2.8 or 6.3mm tabs 	













IEC CONNECTORS

A full range of quality mains rated connectors conforming to IEC and EN 60320 specifications carrying UL, CSA, VDE and other approvals. With electrical ratings up to 20A, 250V (UL) these connectors offer solutions to most mains powered applications. The combinations of

mounting styles and terminations include: flange fixing, snap to panel and PCB mounting together with 2.8/solder tabs, 4.8 and 6.3 faston tabs, screw terminal and PC spill versions. Completing the range are insulating boots, retaining clips and safety covers.

In addition to the standard black moulding, most styles are also available in either white or grey and special colours to match OEM equipment can also be supplied.

<p>PX0587</p> <ul style="list-style-type: none"> IEC C13 connector Straight Female Connector Cable Mounting Rewirable Screw Terminals 10A, 250V ac 	<p>PX0587/SE</p> <ul style="list-style-type: none"> IEC C13 connector Side Entry Female Connector Cable Mounting Rewirable Screw Terminals 10A, 250V ac 	<p>PX0588</p> <ul style="list-style-type: none"> IEC C13 connector Angled Female Connector Cable Mounting Rewirable Screw Terminals 10A, 250V ac
<p>PX0575</p> <ul style="list-style-type: none"> IEC C14 inlet Snap Fit to Panel Fits Panel Sizes 1, 1.5, 2.0 or 3.0mm 2.8, 4.8, 6.3mm Tabs or Screw Terminals 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0579</p> <ul style="list-style-type: none"> IEC C14 inlet Vertical Flange Mount Inlet 2.8, 4.8, 6.3mm Tabs or Screw Terminals 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0580</p> <ul style="list-style-type: none"> IEC C14 inlet Flange Mount Inlet 2.8, 4.8, 6.3mm Tabs or Screw Terminals 10A, 250V ac (15A, 250V ac UL & CSA)
<p>PX0580/PC</p> <ul style="list-style-type: none"> IEC C14 inlet PC Flange Rear Mount Inlet With or Without Rear Cover PC Spills 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PF0001</p> <ul style="list-style-type: none"> IEC C14 inlet Flange Mount Fused Inlet Single Fuse 5 x 20mm Spare Fuse Facility 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac 	<p>PF0011</p> <ul style="list-style-type: none"> IEC C14 inlet Snap Fit to Panel Fused Inlet Single Fuse 5 x 20mm Spare Fuse Facility Panel Sizes 1, 1.5, 2.0 or 3.0mm 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac
<p>PF0030</p> <ul style="list-style-type: none"> IEC C14 inlet Flange Mount Fused Inlet Twin Fused 5 x 20mm 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac 	<p>PX0597</p> <ul style="list-style-type: none"> IEC C15 connector Straight Male Connector Cable Mounting Hot Condition Mates with PX0590 and PX0595 Screw Terminals 10A, 250V ac 	<p>PX0590</p> <ul style="list-style-type: none"> IEC C16 inlet Flange Mount Inlet Hot Condition 2.8 or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA)
<p>PX0690</p> <ul style="list-style-type: none"> IEC C18 inlet Flange Mount Inlet Two Pin Class II (No Earth Pin) 2.8, 4.8, 6.3mm Tabs or Screw Terminals 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PF0006</p> <ul style="list-style-type: none"> IEC C18 inlet Flange Mount Fused Inlet Single Fuse 5 x 20mm Spare Fuse Facility Two Pin Class II (No Earth Pin) 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac 	<p>PX0685</p> <ul style="list-style-type: none"> IEC Sheet E connector Angled Male Connector Cable Mounting Four Position Cable Entry Rewirable Screw Terminals 10A, 250V ac
<p>PX0686</p> <ul style="list-style-type: none"> IEC Sheet E connector Straight Male Connector Cable Mounting Rewirable Screw Terminals 10A, 250V ac 	<p>PX0686/SE</p> <ul style="list-style-type: none"> IEC Sheet E connector Side Entry Male Connector Cable Mounting Rewirable Screw Terminals 10A, 250V ac 	<p>PX0716</p> <ul style="list-style-type: none"> Inlet/Outlet combination Panel Size 1.2mm 4.8mm tabs 10A, 250V ac (15A, 250V ac UL & CSA)
<p>PX0718</p> <ul style="list-style-type: none"> Fused Inlet/Outlet combination 1-6 outlet versions Panel Size 1.5mm Solder tabs 10A, 250V ac (15A, 250V ac UL) All terminals linked 	<p>PX0717</p> <ul style="list-style-type: none"> Snap Fit to Panel 1-7 outlet versions Panel Size 1.5mm Solder Tabs 10A, 250V ac (15A, 250V ac UL) All Terminals Linked 	<p>PX0578/63</p> <ul style="list-style-type: none"> Front of Panel Mount 6.3mm tabs 10A, 250V ac (15A, 250V ac UL)
<p>PX0675</p> <ul style="list-style-type: none"> IEC Sheet F outlet Flange Mount Outlet 2.8mm or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0695</p> <ul style="list-style-type: none"> IEC Sheet F outlet Snap Fit to Panel Outlet Panel Sizes 1, 1.5, 2.0 or 3.0mm 2.8 or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0695/PC</p> <ul style="list-style-type: none"> IEC Sheet F outlet PC Snap Fit to Panel Outlet Panel Sizes 1, 1.5, 2.0 or 3.0mm PC Spills 10A, 250V ac (15A, 250V ac UL & CSA)
<p>PX0793</p> <ul style="list-style-type: none"> IEC Sheet F outlet Flange Mount Outlet Shuttered 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0793/1</p> <ul style="list-style-type: none"> IEC Sheet F outlet Rectangular Flange Mount Outlet Shuttered 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA) 	<p>PX0705</p> <ul style="list-style-type: none"> IEC Sheet F outlet Flange Mount Outlet Two Pin Class II (No Earth Pin) 2.8, 4.8 or 6.3mm Tabs 10A, 250V ac (15A, 250V ac UL & CSA)
<p>RETAINING CLIP KITS</p> <ul style="list-style-type: none"> Prevents Accidental Removal Fits flanged inlets 	<p>BLANKING COVERS</p> <ul style="list-style-type: none"> Blanking covers For Sheet F and Sheet J connectors Protects 'unshielded' connector interfaces against accidental electric shock 	<p>INSULATION BOOTS</p> <ul style="list-style-type: none"> PVC Insulation Boots For Sheet C14 (fused and unfused), Sheet F and Sheet C20 Protects Rear of Connector Protects Against Accidental Electric Shock

 <p>PX0599</p>	<ul style="list-style-type: none"> IEC C19 connector Re-wirable Screw Terminals 12mm max. cable diameter 16A, 250V ac (20A, 250V ac UL and CSA) 	 <p>PX0596</p>	<ul style="list-style-type: none"> IEC C20 inlets Flange mounting 6.3 or 4.8mm tabs 16A, 250V ac (20A, 250V ac UL and CSA) 	 <p>PX0598</p>	<ul style="list-style-type: none"> IEC C20 inlets Snap to panel (1.0, 1.5, 2.0 or 3.0mm) 6.3 or 4.8mm tabs 16A, 250V ac (20A, 250V ac UL and CSA) 
 <p>PX0591</p>	<ul style="list-style-type: none"> IEC Sheet J outlet Flange Mounting 6.3mm Tabs 16A, 250V ac (20A, 250V ac, UL & CSA) 	 <p>PX0592</p>	<ul style="list-style-type: none"> IEC Sheet J outlet Snap Fit to Panel Panel Size 1.5mm 6.3mm Tabs 16A, 250V ac (20A, 250V ac, UL & CSA) 	 <p>PX0593</p>	<ul style="list-style-type: none"> IEC Sheet J outlet Flange Mounting (front of panel) 6.3mm Tabs 16A, 250V ac (20A, 250V ac, UL & CSA) 

With over 26,000 combinations Bulgin's Polysnap mains power inlet modules offer a very adaptable and flexible solution to panel design.

Polysnap allow combinations of mains inlets and outlets, filtered inlets, switches, fuseholders, voltage selectors and indicators mounted in either horizontal or vertical format

bezels ready for quick snap-fit assembly. The compact design occupies the minimum of panel area and a single rectangular mounting hole, offering easy installation for this mains power entry module.

To complement Polysnap the Polyflange range offers a flange fixing alternative for designers who prefer the security of screw fixing.

All types and variations are available through Bulgin's extensive distribution network.

 <p>BZV01/Z0000/01</p>	<ul style="list-style-type: none"> Vertical Module Arrangement Inlet Variations with choice of tag sizes Single Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>BZV01/Z0000/10</p>	<ul style="list-style-type: none"> Vertical Module Arrangement Inlet Variations with choice of tag sizes Double Pole Switch or Indicator Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>BZV03/Z0000/02</p>	<ul style="list-style-type: none"> Vertical Module Arrangement Inlet Variations with choice of tag sizes Single Pole Switch or Neon Indicator Variations Filtered Inlet Option Options of I/O marked switches Non Fused
 <p>BZV45/Z0000/02</p>	<ul style="list-style-type: none"> Outlet with 2.8mm or 6.3mm tags Shuttered or Non-Shuttered Single Pole Switch or Neon Indicator Options of I/O marked switches 	 <p>BZV03/Z0000/07</p>	<ul style="list-style-type: none"> Vertical Module Arrangement Inlet Variations with choice of tag sizes Double Pole Switch/Fuseholder/Indicator/Voltage Selector/Blanking Plate Filtered Inlet Option Options of I/O marked switches 	 <p>BZV03/Z0000/04</p>	<ul style="list-style-type: none"> Vertical Module Arrangement 6.3mm tag version only Fuseholder/Voltage Selector/Indicator/Blanking plate options Filtered Inlet Option
 <p>BZV49/Z0000/C1U</p>	<ul style="list-style-type: none"> Inlet with 4.8mm or 6.3mm tags Single pole circuit breaker Illuminated (red or green) and non-illuminated rocker switch 125Vac and 250Vac Neons 6.3mm tabs on Circuit Breaker 	 <p>BZV09/Z0000/04</p>	<ul style="list-style-type: none"> Vertical Module Arrangement Inlet Variations with choice of tag sizes Filtered Inlet and Blanking Plate options Fused 	 <p>BZV49/Z0000/69</p>	<ul style="list-style-type: none"> C20 inlet with 4.8mm or 6.3mm tags Single Pole Switch marked I/O illuminated, red or green, switches High inrush non-illuminated switch
 <p>BZH09/Z0000/01</p>	<ul style="list-style-type: none"> Horizontal Module Arrangement Inlet Variations with choice of tag sizes Single Pole Switch Variations Filtered Inlet Option Options of I/O marked switches 	 <p>BZH01/Z0000/01</p>	<ul style="list-style-type: none"> Horizontal Module Arrangement Inlet Variations with choice of tag sizes Single Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>BZH01/Z0000/10</p>	<ul style="list-style-type: none"> Horizontal Module Arrangement Inlet Variations with choice of tag sizes Double Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused
 <p>BZM27/Z0000/57B</p>	<ul style="list-style-type: none"> Minimum Combined Bezel Size Horizontal Module Arrangement Inlet Variations with choice of tag sizes Single and Double Pole Switch Variations Filtered Inlet Option 	 <p>BZH11/Z0000/10</p>	<ul style="list-style-type: none"> Horizontal Module Arrangement Inlet Variations with choice of tag sizes Double Pole Switch Variations Filtered Inlet Option Options of I/O marked switches 	 <p>BZH11/Z0000/00</p>	<ul style="list-style-type: none"> Horizontal Module Arrangement Inlet Variations with choice of tag sizes Filtered Inlet Option Fused
 <p>BVA01/Z0000/10</p>	<ul style="list-style-type: none"> Screw Fixing to Panel Vertical Module Arrangement Top/Bottom Fixing Inlet Variations with choice of tag sizes Double Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>BVA01/Z0000/02</p>	<ul style="list-style-type: none"> Screw Fixing to Panel Vertical Module Arrangement Top/Bottom Fixing Inlet Variations with choice of tag sizes Single Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>BVB01/Z0000/01</p>	<ul style="list-style-type: none"> Screw Fixing to Panel Vertical Module Arrangement Side Fixing Inlet Variations with choice of tag sizes Single Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused
 <p>BVB01/Z0000/11</p>	<ul style="list-style-type: none"> Screw Fixing to Panel Vertical Module Arrangement Side Fixing Inlet Variations with choice of tag sizes Double Pole Switch Variations Filtered Inlet Option Options of I/O marked switches Fused 	 <p>EMI FILTER OPTIONS</p>	<ul style="list-style-type: none"> Wide choice of EMI filter options Filter options for all inlet and fused inlets 		

FUSEHOLDERS

Bulgin's extensive range of fuseholders are designed to give the degree of protection demanded in today's sophisticated electronic equipment. Carrying world-wide safety approvals from UL, VDE, CSA and IMQ, all types are manufactured from high grade flame retardant nylon and polyester materials.

Designed primarily for 5 x 20mm and 6.3 x 32mm size fuses with protection against shock to categories PC1, PC2 and PC3. There's a choice of styles for in-line, PCB mounting and panel mounting (screw or snap fit) with terminal options for solder, 2.8mm, 4.8mm or 6.3mm tabs with PC spills.

Dust and waterproof designs provide a front of panel seal up to IP68 in both 5 x 20mm and 6.3 x 32mm size fuses.

Fuse carrier styles include captive drawer, screw cap - with screw driver release, bayonet cap - with screw driver release and screw cap - with finger release.

 <p>FX0415, FX0416</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC2 Fuse Sizes 6.3 x 32mm (FX0415) and 6.3 x 25mm (FX0416) Screw Cap/Hand Release 13A, 250V 16A, 250V UL 	 <p>FX0415/S, FX0416/S</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC2 Fuse Sizes 6.3 x 32mm (FX0415/S) and 6.3 x 25mm (FX0416/S) Screw Cap/Screwdriver Release 13A, 250V 16A, 250V UL 	 <p>FX0417, FX0418</p>	<ul style="list-style-type: none"> Panel Mount or Snap Fit Panel Sizes 1.0 & 1.5 and 2.0 & 3.0mm Touchproof Category PC2 Fuse Size 6.3 x 32mm Screw Cap/Screwdriver Release 16A, 250V, 20A, 250V UL 
 <p>FX0419</p>	<ul style="list-style-type: none"> Panel Sealed to IP68 Touchproof Category PC2 Fuse Size 6.3 x 32mm Screw Cap/Screwdriver/Hand Release 16A, 250V (20A, 250V UL pending)  	 <p>FX0430</p>	<ul style="list-style-type: none"> Snap Fit to Panel Panel Sizes 1.0, 1.5, 2.0 and 3.0mm Touchproof Category PC3 Fuse Size 5 x 20mm Captive Drawer 10A, 250V 16A, 250V UL 	 <p>FX0460</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC3 Fuse Size 5 x 20mm Screw Cap/Screwdriver Release 10A, 250V 16A, 250V UL 
 <p>FX0357, FX0359</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC2 Fuse Size 5 x 20mm Bayonet Cap/Screwdriver Release 10A, 250V 16A, 250V UL 	 <p>FX0367, FX0369</p>	<ul style="list-style-type: none"> Snap Fit to Panel Panel Sizes 1.0 & 1.5 and 2.0 & 3.0mm Touchproof Category PC2 Fuse Size 5 x 20mm Bayonet Cap/Screwdriver Release 10A, 250V 16A, 250V UL 	 <p>FX0454, FX0455</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC2 Fuse Size 5 x 20mm Screw Cap/Screwdriver Release 10A, 250V 16A, 250V UL 
 <p>FX0454/S, FX0455/S</p>	<ul style="list-style-type: none"> Panel Mount Touchproof Category PC2 Fuse Size 5 x 20mm High Profile Bezel Screw Cap/Screwdriver Release 10A, 250V 16A, 250V UL 	 <p>FX0458</p>	<ul style="list-style-type: none"> Snap Fit to Panel Panel Sizes 1.0 & 1.5 and 2.0 & 3.0mm Touchproof Category PC2 Fuse Size 5 x 20mm Screw Cap/Screwdriver Release 10A, 250V 16A, 250V UL 	 <p>FX0354, FX0354/S</p>	<ul style="list-style-type: none"> Panel Mount Low & High Profile Bezels Touchproof Category PC2 Fuse Size 5 x 20mm Screw Cap/Screwdriver Release 6.3A, 250V 
 <p>FX0462, FX0463</p>	<ul style="list-style-type: none"> Panel Sealed to IP68 Touchproof Category PC2 Fuse Size 5 x 20mm Screw Cap/Screwdriver/Hand Release 10A, 250V (16A, 250V UL pending)  	 <p>FX0296/S, FX0296</p>	<ul style="list-style-type: none"> Panel Mount Category PC1 Fuse Sizes 5 x 20mm Screw Cap/Hand Release 6.3A, 250V 	 <p>FX0296/1</p>	<ul style="list-style-type: none"> Panel Mount Category PC1 Fuse Sizes 5 x 20mm Screw Cap/Hand Release 6.3A, 250V 
 <p>FX0345</p>	<ul style="list-style-type: none"> High Profile Panel Mount Sealed to IP66 Category PC1 Fuse Sizes 5 x 20mm Screw Cap/Screwdriver Release 6.3A, 250V  	 <p>FX0365</p>	<ul style="list-style-type: none"> High Profile Panel Mount Sealed to IP66 Category PC1 Fuse Sizes 5 x 20mm Screw Cap/Hand Release Large Cap for Easy Grip 6.3A, 250V  	 <p>FX0461</p>	<ul style="list-style-type: none"> PC Horizontal Mount Touchproof Category PC3 Fuse Size 5 x 20mm Screw Cap/Screwdriver Release PC Spills 10A, 250V 16A, 250V UL 
 <p>FX0457, FX0456</p>	<ul style="list-style-type: none"> PC Horizontal and Vertical Mount Touchproof Category PC2 Fuse Sizes 5 x 20mm Bayonet Cap/Screwdriver Release 10A, 250V 	 <p>FX0330, FX0342</p>	<ul style="list-style-type: none"> PC Horizontal Mount Two or Three PC Spills Category PC1 Fuse Sizes 5 x 20mm Screw Cap/Hand Release 6.3A, 250V 	 <p>FX0442 & FX0443</p>	<ul style="list-style-type: none"> Provide Insulation from Shock on Rear of Fuseholder PVC UL94V-0 Rated Flame Retardant Material 
 <p>FX0321 & FX0267</p>	<ul style="list-style-type: none"> PC or Base Mount Category PC1 Fuse Sizes 5 x 20mm PC Spills - FX0321 Solder Tags - FX0267 6.3A, 250V 	 <p>FX0326, FX0331, FX0360</p>	<ul style="list-style-type: none"> Base Mount Category PC1 Fuse Sizes: <ul style="list-style-type: none"> 6.3 x 32mm (FX0326) 6.3 x 25mm (FX0331) 5 x 20mm (FX0360) 13A, 250V (FX0326 & FX0331) 6.3A, 250V (FX0360) 	 <p>FX0327</p>	<ul style="list-style-type: none"> Base Mount Category PC1 Fuse Sizes 6.3 x 32mm 5A, 250V 
 <p>FX0180, FX0280, FX0380</p>	<ul style="list-style-type: none"> In-Line Category PC1 Fuse Sizes 5 x 20mm, 6.3 x 25mm and 6.3 x 32mm 10A, 50V (250V Inaccessible) 	 <p>FX0185, FX0285, FX0385</p>	<ul style="list-style-type: none"> In-Line Sealed to IP66 Category PC1 Fuse Sizes 5 x 20mm, 6.3 x 25mm and 6.3 x 32mm Screw Terminal (Solder to order) 10A, 50V (250V Inaccessible)  		

Manufactured from Stainless Steel, Bulgin's extensive range of vandal resistant security switches are designed with a high resistance to wear and tear, corrosion and harsh use in potentially hostile environments such as access control applications.

The front and rear panel mounted versions have three profiles – prominent, domed and low profile – with a

























choice of switching and IP66 & 68 front panel sealing that, combined together, meet the ergonomic, electrical and environmental demands of switch panel design. The low profile style switches are now also available with a latching, push on - push off, action.

The dot and ring LED illuminated versions can be driven from 6, 12 and 24V sources, with a variety of illumination

colours and are now available with front and rear of panel sealing options.

Other switch types include conventional push-button and voltage selectors.

Vandal Resistant Switches

 MP0027, MPL027	<ul style="list-style-type: none"> Low profile Stainless steel 28mm dia SPCO Microswitch, 5A 250V (momentary) SPMB, 2A 50V (latching) Mounting hole dia, 26mm 	 MP0027/2	<ul style="list-style-type: none"> Prominent button Stainless steel 28mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 26mm 	 MP0027/3	<ul style="list-style-type: none"> Domed Profile Stainless steel 28mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 26mm
 MP0038, MPL038	<ul style="list-style-type: none"> Low profile Stainless steel 28mm dia SPCO Microswitch, 5A 250V (momentary) SPMB, 2A 50V (latching) Mounting hole dia, 26mm Front panel sealed to IP66 	 MP0038/2	<ul style="list-style-type: none"> Prominent button Stainless steel 28mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 26mm Front panel sealed to IP66 	 MP0038/3	<ul style="list-style-type: none"> Domed Profile Stainless steel 28mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 26mm Front panel sealed to IP66
 MP0025, MPL025	<ul style="list-style-type: none"> Flush with panel Rear panel fixing Stainless steel SPCO Microswitch, 5A 250V (momentary) SPMB, 2A 50V (latching) Mounting hole dia, 23mm 	 MP0025/2	<ul style="list-style-type: none"> Prominent button Rear panel fixing 23mm dia Stainless steel SPCO Microswitch, 5A 250V Mounting hole dia, 23mm 	 MP0025/3	<ul style="list-style-type: none"> Domed Profile Rear panel fixing 23mm dia Stainless steel SPCO Microswitch, 5A 250V Mounting hole dia, 23mm
 MP0034, MPL034	<ul style="list-style-type: none"> Flush with panel Rear panel fixing 19mm dia Stainless steel SPCO Microswitch, 5A 250V (momentary) SPMB, 2A 50V (latching) Mounting hole dia, 19mm 	 MP0034/2	<ul style="list-style-type: none"> Prominent button Rear panel fixing 19mm dia Stainless steel SPCO Microswitch, 5A 250V Mounting hole dia, 19mm 	 MP0034/3	<ul style="list-style-type: none"> Domed Profile Rear panel fixing 19mm dia Stainless steel SPCO Microswitch, 5A 250V Mounting hole dia, 19mm
 MP0031, MPL031	<ul style="list-style-type: none"> Low profile Stainless steel 22mm dia SPCO Microswitch, 5A 250V (momentary) SPMB, 2A 50V (latching) Mounting hole dia, 19mm Front panel sealed to IP66 	 MP0031/2	<ul style="list-style-type: none"> Prominent button Stainless steel 22mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 19mm Front panel sealed to IP66 	 MP0031/3	<ul style="list-style-type: none"> Domed Profile Stainless steel 22mm dia SPCO Microswitch, 5A 250V Mounting hole dia, 19mm Front panel sealed to IP66
 MP0037	<ul style="list-style-type: none"> Low profile Stainless steel 22mm dia SP push to make switch, 1A 50V, screw terminals Mounting hole dia, 19mm Front panel sealed to IP68 	 MP0037/2	<ul style="list-style-type: none"> Prominent button Low profile Stainless steel 22mm dia SP push to make switch, 1A 50V, screw terminals Mounting hole dia, 19mm Front panel sealed to IP68 	 MP0037/3	<ul style="list-style-type: none"> Domed Profile Low profile Stainless steel 22mm dia SP push to make switch, 1A 50V, screw terminals Mounting hole dia, 19mm Front panel sealed to IP68
 MP0013, MP0033	<ul style="list-style-type: none"> Proud fitting Stainless steel 22mm dia SP Push to make switch 1A 50V, screw terminals Mounting hole dia, 19mm MP0033 internally sealed 	 MP0013/2, MP0033/2	<ul style="list-style-type: none"> Proud fitting Prominent button Stainless steel 22mm dia SP Push to make switch 1A 50V, screw terminals Mounting hole dia, 19mm MP0033/2 internally sealed 	<h3>Switch Contact Operation</h3>  <p>S.P. Push to Make S.P.M.B.</p> <p>S.P.C.O.</p>	
 MP0050	<ul style="list-style-type: none"> Low profile or prominent button Stainless steel 32mm dia SP Push to make 5A, 250Vac Mounting hole dia, 27.7mm Front panel sealed to IP68 	 MP0031	<ul style="list-style-type: none"> Low profile Stainless steel 22mm dia D.P.C.O. Microswitch 3A, 125V ac Mounting hole dia, 19mm Front panel sealed to IP66 	 <p>D.P.C.O.</p> <p>S.P.C.O.</p>	

Illuminated Versions

 MPI001	<ul style="list-style-type: none"> Dot illumination Screw terminals or 2.8mm tabs Front panel sealed to IP66 Red, Green, Amber, Blue, White, Red/Green, Red/Blue & Blue/Green LEDs 2, 6, 12 & 24V illumination 22mm dia SP push to make 	 MPI002	<ul style="list-style-type: none"> Ring illumination Screw terminals or 2.8mm tabs Front panel sealed to IP66 Red, Green, Amber, Blue, White, Red/Green, Red/Blue & Blue/Green LEDs 2, 6, 12 & 24V illumination 22mm dia SP push to make 	 MPI002/FL/XX/X	<ul style="list-style-type: none"> Dot or ring illumination Flying lead or solder tag termination 22mm diameter Front and rear panel seal to IP66 2, 6, 12 & 24V illumination Red, Green, Amber, Blue and White illumination Single pole push to make
---	--	---	---	---	--

INDICATORS

This range of panel mounting LED indicators consists of many different bezel styles, types of LED's and colours. The range has developed to meet the many different needs of panel design

including IP66 environmentally sealed versions for use where a front panel seal is needed. The vandal resistant LED indicators are designed to complement the vandal resistant switches, they

have similar profiles with stainless steel bodies, sealing to IP67 and are built to withstand harsh environments.

<p>DX0505 & DX0507</p> <ul style="list-style-type: none"> Proud of Panel Profile Solder Tag/2.8mm Tag or Flying Lead Termination Sealed to IP67 Red, Green, Yellow, Blue or White LED Options Wide Viewing Angle Vandal Resistant 	<p>DX0506 & DX0508</p> <ul style="list-style-type: none"> Flush Panel Profile Solder Tag/2.8mm Tag or Flying Lead Termination Sealed to IP67 Red, Green, Yellow, Blue or White LED Options Wide Viewing Angle Vandal Resistant 	<p>DX0998 DX0999</p> <ul style="list-style-type: none"> 5mm LED Indicators Chrome Plated Brass Bezel Prominent or Recessed Style Choice of LED Types and Colours
<p>DX1120 DX1121</p> <ul style="list-style-type: none"> 5mm LED Indicators Glass Filled Nylon Bezel Prominent or Recessed Style Choice of LED Types and Colours 	<p>DX1090 DX1092</p> <ul style="list-style-type: none"> 5mm LED Indicators Aluminium Bezel, Black Anodised Finish IP66 Front Panel Sealed Prominent or Recessed Style Choice of LED Types and Colours 	<p>DX1091 DX1093</p> <ul style="list-style-type: none"> 5mm LED Indicators Aluminium Bezel, Clear Anodised Finish IP66 Front Panel Sealed Prominent or Recessed Style Choice of LED Types and Colours
<p>DX1116 DX1118</p> <ul style="list-style-type: none"> 4mm LED Indicators Chrome Plated Brass Bezel Prominent or Recessed Style Choice of LED Types and Colours 	<p>DX1117 DX1119</p> <ul style="list-style-type: none"> 4mm LED Indicators Black Nickel Plated Brass Bezel Prominent or Recessed Style Choice of LED Types and Colours 	

GENERAL PURPOSE

This long established series of connectors still find many uses where small, but lower current connections are needed. The range consists of

circular and rectangular styles with 3, 4, 6 and 8 poles, in a choice of configurations, with current ratings up to 6 Amps. The 8 pole round has

become the standard connector for the disco and lighting industry and is available in cable and chassis mounting versions.

<p>PX0551</p> <ul style="list-style-type: none"> Flex Mount Male Circular Connector 8 Poles Mates with PX0552, PX0552/PC, PX0956/S and PX0957/S Screw Terminals 6A, 250V ac (per Pin) 	<p>PX0552</p> <ul style="list-style-type: none"> Panel Mount Female Circular Outlet 8 Poles Mates with PX0551 4.8mm Tabs 6A, 250V ac (per Pin) 	<p>PX0552/PC</p> <ul style="list-style-type: none"> PC Panel Mount Female Circular Outlet 8 Poles Mates with PX0551 PC Spills 6A, 250V ac (per Pin)
<p>PX0956/S</p> <ul style="list-style-type: none"> Flex Mount Female Circular Connector 8 Poles Mates with PX0551, PX0959/P and PX0959/P/PC Screw/Solder Terminals 6A, 250V ac (per Pin) 	<p>PX0957/S</p> <ul style="list-style-type: none"> Panel Mount Female Circular Outlet 8 Poles Mates with PX0551 4.8mm Tabs 6A, 250V ac (per Pin) 	<p>PX0959/P, PX0959/P/PC</p> <ul style="list-style-type: none"> Panel Mount Male Circular Inlet 8 Poles Mates with PX0956/S Solder bucket or PC spills 6A, 250V ac (per Pin)
<p>PX0429</p> <ul style="list-style-type: none"> Circular Inlet 2 Pole + Earth Mates with PX0430/SE and PX0646 Key to Ensure Correct Polarity Solder Tags 3A, 250V ac 	<p>PX0430/SE</p> <ul style="list-style-type: none"> Cable Connector 2 Pole + Earth Mates with PX0429 Key Way to Ensure Correct Polarity Solder Tags 3A, 250V ac 	<p>PX0646</p> <ul style="list-style-type: none"> Circular Connector 2 Pole + Earth Mates with PX0429 Key Way to Ensure Correct Polarity Solder Tags 3A, 250V ac
<p>PX0635</p> <ul style="list-style-type: none"> Circular Male Inlet 6 Pole Mates with PX0636 Key to Ensure Correct Polarity Solder Buckets 3A, 50V ac 	<p>PX0636</p> <ul style="list-style-type: none"> Circular Female Connector 6 Pole Mates with PX0635 Key Way to Ensure Correct Polarity Solder Tags 3A, 50V ac 	<p>SA2403 (3 POLE) SA2367 (4 POLE)</p> <ul style="list-style-type: none"> Cable Male Connector Mates with SA2404 (3 pole) and SA2368 (4 pole) Key to Ensure Correct Polarity Screw Terminals 3A, 250V ac
<p>SA2404 (3 POLE) SA2368 (4 POLE)</p> <ul style="list-style-type: none"> Circular Female Outlet Mates with SA2403 (3 pole) and SA2367 (4 pole) Key Way to Ensure Correct Polarity Solder Buckets 3A, 250V ac 	<p>PX0649</p> <ul style="list-style-type: none"> Circular Male Connector 2 Pole + Earth Mates with PX0650 Solder Buckets 3A, 250V ac 	<p>PX0650</p> <ul style="list-style-type: none"> Circular Female Outlet 2 Pole + Earth Mates with PX0649 Solder Tags 3A, 250V ac

Manufactured from quality mouldings and metal components to ensure a secure and reliable connection, Bulgin's battery holder range caters for battery sizes; AAA(R03), AA(R6), C(R14), D(R20), PP3(6R61) and CR123, accommodating 1, 2, 3 or 4 cells.

There's a choice of fixing styles including screw and flange panel fixing, PCB and base mounting versions.

The panel mounting versions are now available in two styles; standard fixing and front panel sealed to IP67, extending the applications into harsher external environments where dust or

water would inhibit equipment operation. The open frame styles are designed to be either PCB or base mounted and most have an interlocking facility to join adjacent holders together.







Principle applications include portable equipment and memory back-up.

 <p>BXSO11/1</p>	<ul style="list-style-type: none"> Battery size AA (R6) 1, 2 or 3 Cells Flanged Panel Mount Bayonet with finger/coin slot release Front Panel Sealed to IP67 	 <p>BXSO01/1</p>	<ul style="list-style-type: none"> Battery size C (R14) 1, 2 or 3 Cells Panel Mount Screw cap/hand release Front Panel Sealed to IP67 	 <p>BXSO16</p>	<ul style="list-style-type: none"> Battery size D (R20) 1, 2 or 3 Cells Flanged Panel Mount Bayonet/finger release Front Panel Sealed to IP67
 <p>BXO011/1</p>	<ul style="list-style-type: none"> Battery size AA (R6) 1, 2 or 3 Cells Panel Mount Bayonet/Screwdriver release 	 <p>BXO001/1</p>	<ul style="list-style-type: none"> Battery size C (R14) 1, 2 or 3 Cells Panel Mount Screw Cap/Hand release 	 <p>BXO016</p>	<ul style="list-style-type: none"> Battery size D (R20) 1, 2 or 3 Cells Flanged Panel Mount Bayonet/Screwdriver release
 <p>BXO027</p>	<ul style="list-style-type: none"> Battery size AA (R6) 4 Cells Flanged Panel Mount Drawer function 	 <p>BXO023</p>	<ul style="list-style-type: none"> Battery size PP3 (6R61) 1 Cell Flanged Panel Mount Drawer function 	 <p>BXO026</p>	<ul style="list-style-type: none"> Battery size PP3 (6R61) 2 Cells Flanged Panel Mount Drawer function
 <p>BXO034</p>	<ul style="list-style-type: none"> Battery size AAA (R03) 1 Cell PC/Base Mount Open style 	 <p>BXO035</p>	<ul style="list-style-type: none"> Battery size AA (R6) 1 Cell PC/Base Mount Open style 	 <p>BXO036</p>	<ul style="list-style-type: none"> Battery size C (R14) 1 Cell PC/Base Mount Open style
 <p>BXO037</p>	<ul style="list-style-type: none"> Battery size D (R20) 1 Cell PC/Base Mount Open style 	 <p>BXO033</p>	<ul style="list-style-type: none"> Battery size PP3 (6R61) 1 Cell PC/Base Mount Open style 	 <p>BXO123</p>	<ul style="list-style-type: none"> Battery size CR123 1 Cell PC/Base Mount Open style

A range of IP67 rated enclosures designed for electronics and control station applications. Manufactured in UL94V-0 rated polycarbonate and UL94-HB rated ABS. The three sizes are suitable for mounting one, two or three 22mm

components and can be supplied with or without mounting holes. The enclosures are available in black and grey as standard with the option of yellow and transparent lids. Each enclosure also has two M20 pre-formed knock-outs that can be

used with the standard cable glands. Other accessories include a combination mounting foot for use on TS32 & TS35 DIN rail and separate mounting brackets for wall mounting.

 <p>SIZE 1 ENCLOSURE</p>	<ul style="list-style-type: none"> Option for 1 x 22mm hole in lid 80 x 72 x 53mm 2 threaded knock-outs suitable for M20 glands ABS or Flame Retardant Polycarbonate Grey or black base Transparent, smoked grey, black, grey or yellow lid 	 <p>SIZE 2 ENCLOSURE</p>	<ul style="list-style-type: none"> Option for 2 x 22mm hole in lid 80 x 106 x 53mm 2 threaded knock-outs suitable for M20 glands ABS or Flame Retardant Polycarbonate Grey or black base Transparent, smoked grey, black, grey or yellow lid 	 <p>SIZE 3 ENCLOSURE</p>	<ul style="list-style-type: none"> Option for 3 x 22mm hole in lid 80 x 159 x 53mm 2 threaded knock-outs suitable for M20 glands ABS or Flame Retardant Polycarbonate Grey or black base Transparent, smoked grey, black, grey or yellow lid
 <p>ACCESSORIES</p>	<ul style="list-style-type: none"> Combifoot rail mounting accessory to fit TS32 & TS35 DIN rail Snap fixing 	 <p>ACCESSORIES</p>	<ul style="list-style-type: none"> Wall mounting bracket Snap fixing 	 <p>ACCESSORIES</p>	<ul style="list-style-type: none"> Cable glands M20 thread Cable range - 3.5 to 8mm Available in black or grey



bulgin

a brand of Elektron Technology

Europe

Elektron Technology

Woodland Road, Torquay

Devon, UK TQ2 7AY

T +44 (0)1803 407700

F +44 (0)1803 407699

W bulgin.com

E europe@elektron-technology.com

The Americas

Elektron Technology

5856 Corporate Avenue

Suite 220, Cypress, California 90630

T 760-343-3650

F 760-343-3445

W bulgin.com/usa

E americas@elektron-technology.com

Asia

Elektron Technology

3A International Business Park

#08-02 ICON@IBP, Tower A

Singapore 609935

T +65 6933 7680

F +65 6933 7681

W www.elektronapac.com

E asia@elektron-technology.com