

Gear pump

TG-47C-PU-DB4-KA, 24V



Specification

MODEL	TG-47C-PU-DB4-KA,24
VOLTAGE	24V
RATED DELIVERY PRESSURE [MPa]	0.05
RATED DELIVERY PRESSURE [kg/cm ²]	0.5
RATED DELIVERY FLOW [cc/min] (MIN)	350
RATED CURRENT [mA] (MAX)	240

TG-85E-PU-DB4-KA, 24V



Specification

MODEL	TG-85E-PU-DB4-KA,24
VOLTAGE	24V
RATED DELIVERY PRESSURE [MPa]	0.05
RATED DELIVERY PRESSURE [kg/cm ²]	0.5
RATED DELIVERY FLOW [cc/min] (MIN)	220
RATED CURRENT [mA] (MAX)	350

TG-85E-PU-EB4-KA, 24V



Specification

MODEL	TG-85E-PU-EB4-KA,24
VOLTAGE	24V
RATED DELIVERY PRESSURE [MPa]	0.1
RATED DELIVERY PRESSURE [kg/cm ²]	1
RATED DELIVERY FLOW [cc/min] (MIN)	430
RATED CURRENT [mA] (MAX)	500

TG-30S-PU-EB-KA, 24V



Specification

MODEL	TG-30S-PU-EB-KA,24
VOLTAGE	24V
RATED DELIVERY PRESSURE [MPa]	0.1
RATED DELIVERY PRESSURE [kg/cm ²]	1
RATED DELIVERY FLOW [cc/min] (MIN)	1800
RATED CURRENT [mA] (MAX)	1300

TG-21Q-PU-EB-KA, 24V



Specification

MODEL	TG-21Q-PU-EB-KA,24
VOLTAGE	24V
RATED DELIVERY PRESSURE [MPa]	0.1
RATED DELIVERY PRESSURE [kg/cm ²]	1
RATED DELIVERY FLOW [cc/min] (MIN)	1400
RATED CURRENT [mA] (MAX)	1500

Ring pump

RP-K



Specification

DELIVERY FLOW	15, 30, 46, 95, 200 (ml/min)
PUMP HEAD	3m MAX
MOTOR	GEARMOTOR
VOLTAGE	DC24V
CONNECTABLE TUBE	INSIDE DIAMETER 6mm
RATED DELIVERY PRESSURE	0.1MPa/cm ² (1kgf/cm ²)

RP-W



Specification

DELIVERY FLOW	500, 1000 (ml/min)
PUMP HEAD	3m MAX
MOTOR	GEARMOTOR
VOLTAGE	DC24V
CONNECTABLE TUBE	INSIDE DIAMETER 6mm
RATED DELIVERY PRESSURE	0.1MPa/cm ² (1kgf/cm ²)

Rotary actuator

MA



Specification

VOLTAGE	AC/DC24V
WORKABLE RANGE	90°
TORQUE	15Nm (153kg-cm)
SPEED	90° /min
MATERIAL	PBT
WEIGHT	1.2kg

180° and 360° type are not standard products.