

Incremental Magnetic Sensing Head IKS8-Z2P2V24D1R5F1000T1L3C3



Reference Signal: 2
Pole Pitch: 2 mm
Supply Voltage: 7...32 V
Interface: RS422
Resolution: 5 μ m
Output Frequency: 1000 kHz
Cable Type: Standard (\varnothing 4.5 mm)
Cable Length: 3 m
Connector: D SUB 9 (male)

Technical characteristics

- Incremental magnetic sensor
- One block design
- Pole pitch 2 mm
- For linear and rotary scales
- Programmable with PC or App

Benefits

- Non-contact, quick position measurement
- Precise
- Programmable
- No wear from usage
- Resistant to dust, cooling lubricant emulsion, oil, etc.
- Unlimited measuring length

Electrical and mechanical parameter

Pole pitch	
Signal period	2 mm
Resolution	5 μ m
Repeatability	\pm 1 Increment
Voltageg	
Current consumption	65 mA \pm 5 % (UB = 5 V)
Zulässige Last	
Protection class	IP67 (EN 60529)
Operating temperature	-20° ... +70° C
Humidt	
Maximum speed	
Interface	
Cable length	3 m
Connector	D-SUB 9 (male)

Output signals

Output circuit	
Clock frequency	
Tc	
Signal	A, /A, B, /B, Z , /Z
Signal amplitude	5V
Reference voltage U ₀	
Phase shift A and B	90° ± 10° electrical
Maximum frequency (at 2 m/s)	

V+	red
V-	blue
A	brown
/A	green
B	grey
/B	yellow
CK	pink
/CK	white
D	
/D	
SCH	

Dimensions

Magnetics that count

BOGEN 



© BOGEN Electronic GmbH

25.07.2017 21:10

<http://www.bogen-electronic.com/en/magnetic-measurement-solutions/sensing-heads/incremental/linear/00051170.html>

All statements without guarantee. Data can be change at any time.