

Magnetic Sensing Head Linear Absolute SLA2-R1Y1W10E2C1L2

resolution 1 μ m, serial interface SSI, for
10mm scale KBEE10-C134, Analog Signal
sin/cos, cable length: 2 m



Technical characteristics

- Magnetic sensing head with 14 Bit for measuring absolute positions
- For linear scales
- Resolution up to 1 μ m
- Measuring length up to 30 m
- Synchron serial interface (SSI)

Benefits

- Non-contact, quick position measurement
- Precise
- Wearless
- Resistant to dust, cooling lubricant emulsion, oil, etc.
- No wear from usage
- On request with quality protocol
- Resistant to dust, cooling lubricant, emulsion, oil, etc.

Electrical and mechanical parameters

Incremental signal	Sine 1 Vpp
Resolution incremental signal	
Signal period	2 mm
Interface	SSI
Resolution of absolute measurement	1 μm
Repeatability	± 1 increment
Measuring length	30 m
Protection class	IP 67 (EN 60529)
Vibration resistance	200 m/s ² (EN 60068-2-6)
Operating temperature	0 . +50 °C
Storage temperature	-20.+70 °C
Relative humidity	1
Voltage	6 . 28 VDC \pm 5%*
Current consumption	150 mA maximal (R = 120 Ohm)
Maximum cable length	5 m
Maximum travelling speed	5 m
Output signal	Analogue Sin/Cos
Connector	

Output signals

Interface	SSI
Number of data bits	29
Data format	binary
Parity	No
Error bit	No
Output circuit	
Clock frequency	0.1 . 1.2 MHz
Tc	12 . 38 μ s
Signal	A, /A, B, /B
Signal amplitude	
Reference voltage U ₀	~ 2,5 V
Phase shift A and B	90° \pm 10° electrical
Maximum frequency (at 2 m/s)	100 kHz

Cable assignment

V+	red
V-	blue
A	green
/A	orange
B	white
/B	light blue
CK	brown
/CK	yellow
D	pink
/D	grey
SCH	

Dimensions

Mounting tolerance

--

Ordering Code

© BOGEN Electronic GmbH

21.07.2017 22:25

<http://www.bogen-electronic.com/en/magnetic-measurement-solutions/sensing-heads/absolute/linear/00050886.html>

All statements without guarantee. Data can be change at any time.