


PCRP31 POSICHRON[®] Position Sensor Rod Profile with Analog Output



POSICHRON[®] position sensor in a stainless steel pressure case

- Protection class IP68
- Compression-proof up to 15 bar
- Measurement range 0 ... 100 to 0 ... 5750 mm
- Absolute position measurement
- No power for the position magnet
- Wear and maintenance-free
- Cable output
- 0 ... 10 V output
- 4 ... 20 mA output

Discontinued model
Don't use for further developments
Replaced by PCRP32



Specifications		
Output	Voltage: 0 ... 10 V, 3 wire Current: 4 ... 20 mA, 3 wire	
Resolution	Essentially infinite	
Sampling rate	0.5 ... 2 kHz depending on measurement range	
Linearity	±0.1 mm for ranges ≤500 mm ±0.02 % f.s. for ranges >500 mm	
Housing material	Stainless steel 1.4401	
Protection class	IP68, compression-proof up to 15 bar	
Operating temperature	-40 ... +85 °C	
EMC, immunity to interference	EN61326: 1998, Table A1	
EMC, radio frequency emission	EN55011 group 1 class A	
Shock	100 g/s ms according to EN60068-2-27	
Vibration	15 g, 10 ... 2000 Hz according to EN60068-2-6	
Connection	Cable output, standard length 3 m	

Order Code PCRP31

Model Name



Measurement Range (in mm)

100 / 500 / 1000 / 1500 / 2000 / 2500 / 3000 / 4000 / 5000 / 5750
Other ranges on request

Outputs

10V = with 0 ... 10 V signal conditioner (3 wire)
420T = with 4 ... 20 mA signal conditioner (3 wire)

Connection

KAB3M = Cable output, length 3 m (standard)

Order Code Mounting Set (see accessories page 62)

PCRP31-BFS...

Order Code Position Magnet (see accessories page 58)

PCMAG...


Order Example: PCRP31 - 2000 - 10V - KAB3M

PCRP31 POSICHRON[®] Position Sensor Rod Profile with Pulse Output



POSICHRON[®] position sensor in a stainless steel pressure case

- Protection class IP68
- Compression-proof up to 15 bar
- Measurement range 0 ... 100 to 0 ... 5750 mm
- Absolute position measurement
- No power for the position magnet
- Wear- and maintenance-free
- Cable output
- Pulse output (start/stop)



Specifications		
Output		Pulse output (start/stop)
Resolution		Essentially infinite
Sampling rate		0.5 ... 2 kHz depending on measurement range
Linearity		±0.1 mm for ranges ≤500 mm ±0.02 % f.s. for ranges >500 mm
Housing material		Stainless steel 1.4401
Protection class		IP68, compression-proof up to 15 bar
Operating temperature		-40 ... +85 °C
EMC, immunity to interference		EN61326: 1998, Table A1
EMC, radio frequency emission		EN55011 group 1 class A
Shock		100 g/s ms according to EN60068-2-27
Vibration		15 g, 10 ... 2000 Hz according to EN60068-2-6
Connection		Cable output, standard length 3 m

Order Code PCRP31

Model Name PCRP31 - - -

Measurement Range (in mm)
100 / 500 / 1000 / 1500 / 2000 / 2500 / 3000 / 4000 / 5000 / 5750
Other ranges on request

Output
STSP = with pulse output (start/stop)

Connection
KAB3M = Cable output, length 3 m (standard)

Order Code Mounting Set (see accessories page 62)

PCRP31-BFS...

Order Code Position Magnet (see accessories page 58)

PCMAG...


Order Example: PCRP31 - 1500 - STSP - KAB3M

PCRP31 POSICHRON[®] Position Sensor Rod Profile with SSI Output



POSICHRON[®] position sensor in a stainless steel pressure case

- Protection class IP68
- Compression-proof up to 15 bar
- Measurement range 0 ... 100 to 0 ... 5750 mm
- Absolute position measurement
- No power for the position magnet
- Wear- and maintenance-free
- Cable output
- Synchronous serial output (SSI)



Specifications		Synchronous serial (SSI)
Output		Synchronous serial (SSI)
Resolution		Typ. 2 µm
Sampling rate		0.5 ... 2 kHz depending on measurement range
Linearity		±0.1 mm for ranges ≤500 mm ±0.02 % f.s. for ranges >500 mm
Housing material		Stainless steel 1.4401
Protection class		IP68, compression-proof up to 15 bar
Operating temperature		-40 ... +85 °C
EMC, immunity to interference		EN61326: 1998, Table A1
EMC, radio frequency emission		EN55011 group 1 class A
Shock		100 g/6 ms according to EN60068-2-27
Vibration		15 g, 10 ... 2000 Hz according to EN60068-2-6
Connection		Cable output, standard length 3 m

Order Code PCFP23

Model Name

Measurement Range (in mm)


100 / 500 / 1000 / 1500 / 2000 / 2500 / 3000 / 4000 / 5000 / 5750
Other ranges on request

Output

SSI = with synchronous serial output (SSI)

Connection

KAB3M = Cable output, length 3 m (standard)



Order Code Mounting Set (see accessories page 62)

PCRP31-BFS...

Order Code Position Magnet (see accessories page 58)

PCMAG...


Order Example: PCRP31 - 1500 - SSI - KAB3M

PCRP31 POSICHRON[®] Position Sensor

Rod profile with pressure case



Outline drawing




Dimensions informative only
For guaranteed dimensions consult factory!


POSICHRON® Output Specification 420T and 10V



Signal Conditioner 420T Current output (3 wire)	Excitation voltage	+18...+27 V DC, residual ripple 10 mV _{SS}
	Excitation current	80 mA max.
	Load resistor	350 Ω max.
	Output current	4 ... 20 mA equivalent to 0 ... 100% range
	Stability (temperature)	±50 x 10 ⁻⁶ / °C full scale
	Protection	Reverse polarity, permanent short circuit
	Output noise	0.5 mV _{RMS}
	Operating temperature	-40 ... +85 °C
	Immunity to interference (EMC)	According to EN 61326: 1998



Signal conditioner 10V Voltage output (3 wire)	Excitation voltage	+18 ... +27 V DC, residual ripple 10 mV _{SS}
	Excitation current	80 mA max.
	Output voltage	0 ... +10 V DC equivalent to 0 ... 100% range
	Output current	2 mA max.
	Output load	> 5 kΩ
	Stability (temperature)	±50 x 10 ⁻⁶ / °C full scale
	Protection	Reverse polarity, permanent short circuit
	Output noise	0,5 mV _{RMS}
	Operating temperature	-40 ... +85 °C
Immunity to interference (EMC)	According to EN 61326: 1998	



Signal Wiring	Output signals	Connector	Cable colour	
	420T	10V		pin no.
	Excitation +	Excitation +	1	white
	Excitation GND	Excitation GND	2	brown
	Signal +	Signal +	3	green
		Signal GND	4	yellow

Connection
Mating Connector


View to sensor
connector

POSICHRON® Output Specification Pulse Interface




Pulse interface STSP (start/stop) 	Excitation voltage	+18 ... +27 V DC, residual ripple 10 mV _{SS}
	Excitation current	150 mA max.
	Stability (temperature)	±50 x 10 ⁻⁶ / °C full scale
	Wave velocity	2850 ... 2950 m/s
	Level INIT and START/STOP	RS 485 / RS 422
	Protection	Reverse polarity, short circuit
	Operating temperature	-40 ... +85 °C
	EMC, interference resistance	EN61326: 1998, Table A1
EMC, emitted interference	EN55011 Group 1 Class A	

Signal Diagram



The subsequent circuit generates a signal on the INIT line. The position sensor answers with a START and a STOP signal.

$$\text{Position value } x = t(x) \cdot v_s$$




The position value will be calculated by multiplication of the time interval $t(x)$ with the conversion factor specified on the type label.


Signal wiring / connection	Pulse interface	Connector pin no.	Cable colour
	Excitation +	1	white
	Excitation GND	2	brown
	INIT +	3	green
	INIT -	4	yellow
	STSP +	5	grey
	STSP -	6	pink
	Shield	Contact via connector housing	black

Mating connector

View to sensor connector



WS-CONN-D8



CONN-M12-8P-X


POSICHRON[®] Output Specification SSI



Description

The data transmission takes place by means of the two signals CLOCK and DATA. The processing unit (PLC, Microcomputer) sends pulse sequences which clocks the data transmission at the required transfer rate. With the first falling edge of the pulse sequence the position of the sensor is recorded and stored. The following rising edges control the bit-by-bit transmission of the data word. After a delay time the next new position information will be transmitted.

Data Format (Train of 26 pulses)




SSI (synchronous serial)



Output	EIA RS-422, RS-485, short-circuit proof
Excitation Voltage	+12 ... +27 V DC, residual ripple 10 mV _{SS}
Excitation Current	150 mA max. without load
Clock Frequency	100 kHz ... 1 MHz
Code	Gray 24 bit, continuous progression
Resolution	2 µm max.
Delay between Pulse Trains	>25 µs
Stability (Temperature)	±20 x 10 ⁻⁶ / °C full scale
Operation Temperature	-40 ... +85 °C
Immunity to Interference (EMC)	According to EN50082-2, EN50081-1

Signal diagram



Cable length	Baud rate
50 m	100 ... 1000 kHz
100 m	100 ... 300 kHz

Note:
Extension of the cable length will reduce the maximum transmission rate.
The signals CLOCK/CLOCK and DATA/DATA must be connected in a twisted pair cable, shielded per pair and common.

Signal Wiring / Connection

Signal name	Connector pin no.	Cable colour
Excitation +	1	white
Excitation GND (0V)	2	brown
CLOCK	3	green
CLOCK	4	yellow
DATA	5	grey
DATA	6	pink

