

# Product Data Sheet



## R6J60AXB

Replace "X" with 1, 2 or 3 for number of poles

### Reinforced Class J Fuse Holder 60 Amps, 600 Volts AC/DC



#### Wire Range:

- #2 - #14 AWG Copper
- #2 - #14 AWG Aluminum

#### Holds fuse size 1 1/16" diameter X 2 3/8"

Commonly used fuses in this holder: A4J, AJT, JKS, JLS, JTD, JTD\_ID, LPJ

[See tables below for wire sizes.](#)

#### Electrical Ratings:

- 31 - 60A max (amperage rating based on maximum fuse rating for that physical size)
- 600 Volts AC/DC
- Approved for 200,000 Amp Withstand Rating

#### Mechanical Ratings:

- Insulator base temperature rating: -40°C/F to 125°C (257°F) UL RTI
- Flammability rating of insulator base: UL 94 V-0
- Touch protection: IP-20 (IEC 60529) with optional cover CJ660 (See accessories)
  - Use outside these ratings needs to be judged in the end-use application.

#### Materials:

- Fuse Clip: Copper alloy, tin plated
- Box Connector: High conductivity aluminum, tin plated
- Reinforcing Spring: Steel, tin plated
- Insulator base: Glass filled polycarbonate (thermoplastic)
- Terminal set screws: Aluminum, nickel plated
- Connector mounting screws: Steel, zinc plated

#### Agency Approvals:

- UL Listed, Fuseholder standards UL 4248-1 and UL 4248-8.
- UL File No. IZLT.E35113
- CSA Certified, CSA C22.2 No. 39 – M1987, File No. LR21455
- CE compliant to IEC 60947-1
- RoHS Compliant


**Wire Approvals:**

Wire Size	Torque		Copper Wire Stranding Classes - Number of Conductors		
	N-m	In. lb.	Solid	Class B	Class C
2 AWG	5.6	50 in. lbs		1	1
4	5.1	45 in. lbs		1	1
6	5.1	45 in. lbs		1	1
8	4.5	40 in. lbs		1	1
10	4.0	35 in. lbs	1	1	1
12	4.0	35 in. lbs	1	1	1
14	4.0	35 in. lbs	1	1	1

- Wire strip length – 9/16”
- Panel mountable: #1/4 fastener, torque to 30-40 in. lbs. (3.4 - 4.5 N-m)

**Accessories:**

- Cover: CJ660. Glass-filled polycarbonate (thermoplastic). 125°C (UL RTI), Flammability rating UL 94 V-0, UL Listed File No. JDVS2.181825.



[WWW.MARATHONSP.COM](http://WWW.MARATHONSP.COM)  
1-419-352-8441