



Working Load Limit (WLL) 7, 11,15, 22, 30, 37, 45, 60 Tons

Rovsco ROV Hooks are specifically designed for ROV use, to release or move heavy equipment in the deep ocean, or to retrieve back to the surface equipment from the deep ocean.

Rovsco's ROV Hooks provide extremely reliable and trouble free operation. Their unique design maintains full integrity of the hook and incorporates many safety features that prevent any accidental release of the load during handling. The operation requires just a few simple steps through the use of a manipulator.

Rovsco's ROV Hooks are painted bright yellow which makes them clearly visible in the ocean and helps in achieving the safety objectives of the subsea operations.



#### **Features**

- Designed for ROV operation
- ◆ Reliable


## **Applications**

- ♦ Release of equipment in the ocean
- Retrieve equipment from ocean

### **Load Certification**

Available for twice the load ratings





# All dimensions are in inches

| Hook<br>Tons | С     | D     | F    | G    | J    | K    | М    | N    | Q    | AA   | Weight<br>(lbs) |
|--------------|-------|-------|------|------|------|------|------|------|------|------|-----------------|
| 5            | 5.77  | 4.81  | 2.00 | 1.44 | 1.36 | 1.31 | 1.31 | 0.72 | 1.56 | 2.50 | 8.50            |
| 7            | 7.37  | 6.27  | 2.50 | 1.81 | 1.61 | 1.66 | 1.66 | 0.90 | 2.00 | 3.00 | 12.80           |
| 11           | 9.07  | 7.45  | 3.00 | 2.25 | 2.08 | 1.88 | 1.63 | 1.11 | 2.44 | 4.00 | 20.00           |
| 15           | 10.08 | 8.30  | 3.25 | 2.59 | 2.27 | 2.19 | 1.94 | 1.27 | 2.84 | 4.00 | 27.10           |
| 22           | 12.53 | 10.30 | 4.25 | 3.00 | 3.02 | 2.69 | 2.38 | 1.56 | 3.50 | 5.00 | 47.50           |
| 30           | 14.06 | 13.62 | 5.00 | 3.62 | 3.25 | 3.00 | 3.00 | 1.75 | 3.50 | 6.50 | 69.50           |
| 37           | 18.19 | 14.06 | 5.38 | 4.56 | 3.00 | 4.00 | 3.19 | 2.00 | 4.50 | 7.00 | 115.00          |
| 45           | 20.12 | 15.44 | 6.00 | 5.06 | 3.38 | 4.50 | 3.25 | 2.18 | 4.94 | 8.00 | 167.00          |
| 60           | 23.72 | 18.50 | 7.00 | 6.00 | 4.12 | 5.50 | 3.91 | 2.53 | 5.69 | 10.0 | 250.00          |

All specifications are subject to change without notice in line with Rovsco's policy of continued product development

ROVSCO<sup>®</sup>, Inc.
5263 Barker Cypress Road, Suite 600 P.O. Box 218570 Houston, Texas 77218-8570 U.S.A.

Tel: +1 281 858 6333 Fax: +1 281 858 6363 Email: sales@rovsco.com http://www.rovsco.com