

# WIRELESS ANEMOMETER WITH ALARMS FOR CONSTRUCTION SITES AND INDUSTRY


W410/D  
W410XB/D



## FEATURES

- extremely easy mounting due to wireless sensor and magnetic mounting (optional accessories)
- up to 500 m range with standard range sensor
- up to 1300 m range with extended range sensor
- built-in audible alarm and red/yellow alarm lights
- 4 programmable alarm relay outputs with ON and OFF delays
- 2-zone wind direction alarm
- back lighted graphic LCD with large numbers
- magnetic mounting (optional accessories)
- Bluetooth output signal for smart devices via free application (W410XB/D model)

## HISTORY DISPLAYS



## FUNCTIONS

- current wind speed
- wind direction
- bar graph for current wind speed
- bar graph for peak wind speed
- 8 h wind speed history graph
- 8 h alarm history graph
- temperature

## APPLICATIONS

- crane applications
  - mobile cranes
  - tower cranes
  - bridge cranes
- lift applications
- all applications where wind alarm is needed



NAVIS

#### COMPATIBLE SENSORS:



WS 010-1 (standard range WS sensor)  
WS 011-1 (extended range WS sensor)



WSD 010-1 (standard range WSD sensor)  
WSD 011-1 (extended range WSD sensor)

#### ORDERING:

##### Display unit

- 1 **W410/D** display unit
- 2 **W410XB/D** display unit, BLE compatibility

##### Sets with sensors included

- 3 **W410/WS** display unit, standard range WS sensor
- 4 **W410XB/WS** display unit, extended range WS sensor, BLE compatibility
- 5 **W410/WSD** display unit, standard range WSD sensor
- 6 **W410XB/WSD** display unit, extended range WSD sensor, BLE compatibility



1, 2



3



4



5



6

#### OPTIONS

Wind tunnel certificated version available

#### OPTIONAL ACCESSORIES

- 1 External antenna with 4 m cable, magnetic mounting
- 2 YAGI antenna

#### MOUNTING ACCESSORIES

- 3 Display magnetic mounting assembly



1



2



3



NAVIS

#### TECHNICAL DATA

<b>Wind speed measurement range:</b>	0,6...50 m/s
<b>Wind direction measurement range:</b>	0°– 359° (6 ° graph resolution)
<b>Temperature measurement range:</b>	-30....+60 °C
<b>Wind speed units:</b>	m/s, km/h, knots, mph
<b>Temperature units:</b>	°C, °F
<b>Wind speed averaging period:</b>	selectable 2 s, 10 s, 30 s
<b>Wind direction averaging period:</b>	10 s
<b>Wind speed resolution:</b>	0,1 m/s
<b>Wind direction resolution:</b>	6°
<b>Temperature resolution:</b>	1°C
<b>Wind speed accuracy:</b>	+/- 2,5 %, calibration possible in 0,5% steps
<b>Wind direction accuracy:</b>	+/- 2,5°, adjustable offset +/- 180°
<b>Temperature accuracy:</b>	+/- 1°C
<b>Communication frequency :</b>	868 MHZ
<b>Antenna input:</b>	50 Ohm, SMA connector
<b>Range:</b>	
- with standard range sensor	up to 500 m visible distance
- with extended range sensor	up to 1300 m visible distance
- with Yagi antenna	3-4 x nominal range
<b>Operating voltage:</b>	12 - 24 V DC
<b>Power consumption:</b>	max. 300 mA
<b>Temperature operating range:</b>	-30 ... +60 °C
<b>Outputs:</b>	4 x relay, contact rating 2 A/24 V, programable ON and OFF delays
<b>Alarms:</b>	adjustable max. alarm red light + continuous sound signal adjustable pre. alarm yellow light + interrupted sound signal
<b>Sound signal (integrated buzzer):</b>	85 dB/10 cm
<b>Dimensions:</b>	150 x 80 x 55 mm
<b>Weight:</b>	260 g

#### ADDITIONAL FOR W410XB

<b>Transmission distance from display unit to smart device:</b>	up to 30 m
<b>Analog signal outputs:</b>	2 x 4...20 mA (not isolated, common ground with supply) 4 mA = 0 m/s (0° ) 20 mA = programmable 10 - 50 m/s (359°)

Android application requires device with 4.3 OS or newer with Bluetooth BLE.

