



DC Contactor Relay(CTS60~125)

Specifications

Spec	CTS60	CTS80	CTS100	CTS125
Coil Data				
Rated voltage	6 - 110VDC	6 - 110VDC	6 - 110VDC	6 - 110VDC
Pick-up voltage	75% max(Nominal voltage)	75% max(Nominal voltage)	75% max(Nominal voltage)	75% max(Nominal voltage)
Drop out voltage power to set	10% min(Nominal voltage)	10% min(Nominal voltage)	10% min(Nominal voltage)	10% min(Nominal voltage)
Coil power consumption	5 to 8(Watts)	5 to 8(Watts)	5 to 8(Watts)	5 to 8(Watts)
Contact data				
Max.current(A)	60A	80A	100A	125A
Max.contact voltage	250VDC	250VDC	250VDC	250VDC
Max.contact current	90A at 96VDC	120A at 96VDC	150A at 96VDC	187.5A at 96VDC
Contact closes time voltage	20ms	20ms	20ms	20ms
Ambient temperature	-40 ~ 60°C	-40 ~ 60°C	-40 ~ 60°C	-40 ~ 60°C
Aux. switch	DT, 5A at under 250VAC	DT, 5A at under 250VAC	DT, 5A at under 250VAC	DT, 5A at under 250VAC



İmaj Teknik Elektrik Elektronik San. ve Tic. Ltd. Şti.

EMEKYEMEZ MAH.TUTSAK SOK. NO: 16/13-14-15
KARAKOY/İSTANBUL
TURKEY

Telefon : +90 212 235 9535 / 36
Fax : +90 212 235 9537

www.imajteknik.com
www.imajteknik.com.tr