

EXPERTS IN
ENERGY MEASUREMENT
TECHNOLOGY



SHORT PRODUCT OVERVIEW

Janitza[®]

GridVis® SOFTWARE

Energy management, power quality, residual current monitoring:

Visualising, analysing, generating alerts, documenting

Energy management (EnMS)

Certified according to ISO 50001. You are on the safe side when it comes to topics, such as BAFA, reduction of EEG apportionments or even the peak balancing according to the German Energy-Saving Efficiency System Ordinance (SpaEfV).

Transparency

Gain an overview of consumption data and costs. Uncover increasing residual currents and overloads. Generate key performance indicators from consumption and measured data according to the provisions of ISO 50006.

Network analysis & evaluation

Analyse and evaluate measured data. Functions: statistics, line charts, pie charts, heat maps, CBEMA curves, duration curves, tables, Sankey diagram, key performance indicators.

Security & alarm management

Monitor threshold values of measured variables, consumption data, residual currents and communication. Reliable alerting via e-mail and web interface.

Visualisation & documentation

Create your own dashboards and overviews with a large selection of functions and graphics. Profit from the prepared reports and documentation for the topics of energy management, power quality and residual current monitoring.



Dashboard example

OVERVIEW OF GridVis® EDITIONS

GridVis®-Basic – free basic version

51.00.116

- Event browser (NEW¹¹)
- Maximum five measurement devices
- Graphs and analysis tools
- Database (Jan-DB)
- Reports:
 - Commissioning report
 - Energy and consumption reports
 - PQ reports (EN 50160, EN 61000-2-4 etc.)
 - RCM report

GridVis®-Professional

51.00.160

As GridVis®-Basic, but with the following additional features:

- Unlimited number of devices and data points
- Database drivers (MSSQL, MySQL)
- Automation (reading, timing, etc.)
- Virtual measurement devices and logic
- User management

GridVis®-Service

51.00.180

As GridVis®-Professional, but with the following additional features:

- Active directory (NEW¹¹)
- Expanded reports:
 - Utilization report (NEW¹¹)
 - Uptime
 - LET (Limits, Event, Transients)
 - Energy invoice
- COMTRADE data export
- MSCONS data import (NEW¹¹) and export
- Service including REST API
- Online recorder
- Alarm management
- Measured and consumption data export (CSV)
- External devices (generic Modbus)
- Expanded automation (reports, database actions, E-mail/alerting, cost centers and tariffs)

GridVis®-Ultimate

51.00.190

As GridVis®-Service, but with the following additional features:

- GridVis® Energy web interface
- Expanded user management
- Dashboard and template manager
- Widgets
- Key performance indicator evaluation (KPI)
- Sankey diagram (energy flow analysis)
- Device overview with graph function
- OPC UA client
- Image and symbol library

¹¹ NEW: from version 7.4

Janitza®



Type	UMG 103-CBM (UL certified)
Item number	52,28,001
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	277 / 480 V AC
Use in three-phase 3-conductor systems ungrounded up to a max.	-
Supply voltage	-
Three-conductor / four-conductor (L-N, L-L)	- / •
Quadrants	4
Sampling rate 50/60 Hz	5.4 kHz
National certification according to PTB-A 50.7	-
Effective value from periods (50/60 Hz)	10 / 12
Residual current inputs	-
Current measuring channels	3
Thermistor input	-
Harmonics V / A	1. – 40.
Distortion factor THD-U / THD-I in %	•
Unbalance	-
Short-term flicker / long-term flicker	-
Transients	-
Short-term interruptions	-
Accuracy V; A	0.2%; 0.2%
Class A per EN 61000-4-30	-
Active energy class	0.5S (.../5 A)
Digital inputs	-
Digital / pulse output	-
Analogue output	-
Memory min. / max. values	•
Memory size	4 MB
Clock	•
Integrated logic	Comparator
Web server / e-mail	-
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-
Fault recorder function	-
Peak load optimisation	-
Software for energy management and network analysis	GridVis®-Basic
Interfaces	
RS232	-
RS485	•
USB	-
D-Sup-9-connector (Profibus)	-
M-Bus	-
Ethernet	-
Protocols	
Modbus RTU	•
Modbus gateway	-
Profibus DP V0	-
Modbus TCP/IP, Modbus RTU over Ethernet	-
SNMP	-
OPC UA	-
BACnet IP	-
Profinet	-

UMG 103-CBM

Compact energy analyzer

- : included
- : not included

*1 Other voltages are also available as options

*2 Option

*3 Combination options for inputs and outputs:
a) 5 digital outputs
b) 2 Digital outputs and 3 digital inputs

*4 Combined function:
optional analogue / temperature / residual current input

*5 2 Pulse outputs

*6 SNMP only for internal PROFINET communication

*7 With module + 1 current measurement channel

*8 MID certified

*9 On the basic device

*10 For polling the slave device

*11 Combined function:
optional operating current or residual current

*12 These are 4...20 mA signal inputs

*13 230 / 400 V AC (acc. to UL) at MID/MID+ variants

Comment: For detailed technical information please refer to the respective operation manuals and the Modbus address lists.

Janitza®



&



Type	UMG 20CM	Module 20CM-CT6
Item number	14.01.625	14.01.626
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	230 / 400 V AC	Only current measurement
Use in three-phase 3-conductor systems ungrounded up to a max.	-	-
Supply voltage	90 – 276 V AC; 90 – 276 V DC	-
Three-conductor / four-conductor (L-N, L-L)	•/•	- / •
Quadrants	4	4
Sampling rate 50/60 Hz	20 kHz	60 kHz
National certification according to PTB-A 50.7	-	-
Effective value from periods (50/60 Hz)	10 / 12	10 / 12
Residual current inputs	20 ^{III}	6 ^{III}
Current measuring channels	20 ^{III}	6–96 (max. 16 modules) ^{III}
Thermistor input	-	-
Harmonics V / A	1. – 63.	1. – 63.
Distortion factor THD-U / THD-I in %	•	only THD-I
Unbalance	-	-
Short-term flicker / long-term flicker	-	-
Transients	-	-
Short-term interruptions	-	-
Accuracy V; A	1%; 1%	- ; 0.5%
Class A per EN 61000-4-30	-	-
Active energy class	1	2
Digital inputs	-	-
Digital / pulse output	2	-
Analogue output	-	-
Memory min. / max. values	•	•
Memory size	768 KB	only via UMG 20CM
Clock	•	only via UMG 20CM
Integrated logic	Current threshold values per channel	Current threshold values per channel
Web server / e-mail	-	-
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-	-
Fault recorder function	-	-
Peak load optimisation	-	-
Software for energy management and network analysis	GridVis®-Basic	GridVis®-Basic
Interfaces		
RS232	•	-
RS485	•	only via UMG 20CM
USB	-	-
D-Sup-9-connector (Profibus)	-	-
M-Bus	-	-
Ethernet	-	-
Protocols		
Modbus RTU	•	only via UMG 20CM
Modbus gateway	-	-
Profibus DP V0	-	-
Modbus TCP/IP, Modbus RTU over Ethernet	-	-
SNMP	-	-
OPC UA	-	-
BACnet IP	-	-
Profinet	-	-

UMG 20CM

Multichannel operating current and residual current measurement device

Module 20CM-CT6

Modular expansion for the UMG 20CM

Janitza®

Type	UMG 604-PRO (UL certified)		UMG 605-PRO (UL certified)
Item number	E 52.16.202	EP 52.16.201	52.16.227
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	277 / 480 V AC		277 / 480 V AC
Use in three-phase 3-conductor systems ungrounded up to a max.	480 V AC		480 V AC
Supply voltage	95 – 240 V AC; 135 – 340 V DC*1		95 – 240 V AC; 135 – 340 V DC*1
Three-conductor / four-conductor (L-N, L-L)	• / •		• / •
Quadrants	4		4
Sampling rate 50/60 Hz	20 kHz		20 kHz
National certification according to PTB-A 50.7	-		-
Effective value from periods (50/60 Hz)	10 / 12		10 / 12
Residual current inputs	-		-
Current measuring channels	4		4
Thermistor input	1		1
Harmonics V / A	1. – 40.		1. – 63.
Distortion factor THD-U / THD-I in %	•		•
Unbalance	•		•
Short-term flicker / long-term flicker	-		•
Transients	> 50 µs		> 50 µs
Short-term interruptions	•		•
Accuracy V; A	0.2%; 0.25%		0.2%; 0.25%
Class A per EN 61000-4-30	-		-
Active energy class	0.5S (.../5 A)		0.5S (.../5 A)
Digital inputs	2		2
Digital / pulse output	2		2
Analogue output	-		-
Memory min. / max. values	•		•
Memory size	128 MB		128 MB
Clock	•		•
Integrated logic	Jasic® (7 Prg.)		Jasic® (7 Prg.)
Web server / e-mail	• / •		• / •
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	•		•
Fault recorder function	•		•
Peak load optimisation	•*2		•*2
Software for energy management and network analysis	GridVis®-Basic		GridVis®-Basic
Interfaces			
RS232	•		•
RS485	•		•
USB	-		-
D-Sup-9-connector (Profibus)	-		•
M-Bus	-		-
Ethernet	•		•
Protocols			
Modbus RTU	•		•
Modbus gateway	•		•
Profibus DP V0	-		•
Modbus TCP/IP, Modbus RTU over Ethernet	•		•
SNMP	•		•
OPC UA	-		-
BACnet IP	•*2		•*2
Profinet	-		-



UMG 604-PRO

Functionally expandable power analyzer

UMG 605-PRO

Power quality analyzer (Class S according to IEC 61000-4-30)

Janitza®

Type	UMG 801	Module 800-CT8-A
Item number	52.31.001	52.31.201
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	347 / 600 V AC (acc. to UL) 480 / 830 V AC (acc. to IEC)	Only current measurement
Use in three-phase 3-conductor systems ungrounded up to a max.	690 V AC	
Supply voltage	24 – 48 V DC, PELV	
Three-conductor / four-conductor (L-N, L-L)	• / •	
Quadrants	4	4
Sampling rate 50/60 Hz	51.2 kHz (V) / 25.6 kHz (A)	8.33 kHz
National certification according to PTB-A 50.7	-	-
Effective value from periods (50/60 Hz)	10 / 12	10 / 12
Residual current inputs	4*4	
Current measuring channels	8	8–80 (max. 10 modules)
Thermistor input	4*4	
Harmonics V / A	1.–127. / 1.–63.	1., 3., 5. ... 15.
Distortion factor THD-U / THD-I in %	•	only THD-I
Unbalance	•	
Short-term flicker / long-term flicker	-	
Transients	-	
Short-term interruptions	-	
Accuracy V; A	0.2%; 0.2%	0.5%
Class A per EN 61000-4-30	-	
Active energy class	0.2S (.../5 A)	0.5S (.../5 A)
Digital inputs	4	
Digital / pulse output	4	
Analogue output	1	
Memory min. / max. values	•	*9
Memory size	4 GB	
Clock	•	*9
Integrated logic	-	
Web server / e-mail	-	
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-	
Fault recorder function	-	
Peak load optimisation	-	
Software for energy management and network analysis	GridVis®-Basic	GridVis®-Basic
Interfaces		
RS232	-	
RS485	•	*9
USB	•	
D-Sup-9-connector (Profibus)	-	
M-Bus	-	
Ethernet	2	*9
Protocols		
Modbus RTU	•	*9
Modbus gateway	•*10	
Profibus DP V0	-	
Modbus TCP/IP, Modbus RTU over Ethernet	Modbus TCP/IP	*9
SNMP	-	
OPC UA	•	*9
BACnet IP	-	
Profinet	-	

UMG 801

Modularly expandable energy measurement device



&

Module 800-CT8-A

Modular expansion for the UMG 801



Module 800-CT8-A (UL certified)

Janitza®

Type	UMG 806 modules		
	806-EC1	806-ED1	806-EI1
Item number	14.02.015	14.02.016	14.02.020
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	230 / 400 V AC		
Use in three-phase 3-conductor systems ungrounded up to a max.	400 V AC		
Supply voltage	80 – 270 V AC; 80 – 270 V DC		
Three-conductor / four-conductor (L-N, L-L)	• / •		
Quadrants	4		
Sampling rate 50/60 Hz	8 kHz		
National certification according to PTB-A 50.7	-		
Effective value from periods (50/60 Hz)	10 / 12		
Residual current inputs	1		
Current measuring channels	4		4 ¹²
Thermistor input	1		
Harmonics V / A	1. – 31.		
Distortion factor THD-U / THD-I in %	•		
Unbalance	•		
Short-term flicker / long-term flicker	-		
Transients	-		
Short-term interruptions	-		
Accuracy V; A	0.2%; 0.2%		
Class A per EN 61000-4-30	-		
Active energy class	0.5S (.../5 A)		
Digital inputs	-	4	
Digital / pulse output	1	2	2
Analogue output	-		
Memory min. / max. values	•		
Memory size	4 MB		
Clock	•		
Integrated logic	-		
Web server / e-mail	-		
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-		
Fault recorder function	-		
Peak load optimisation	-		
Software for energy management and network analysis	GridVis®-Basic		GridVis®-Basic
Interfaces			
RS232	-		
RS485	•		
USB	-		
D-Sup-9-connector (Profibus)	-		
M-Bus	-		
Ethernet	-	•	
Protocols			
Modbus RTU	•		
Modbus gateway	-		
Profibus DP V0	-		
Modbus TCP/IP, Modbus RTU over Ethernet	-	•	
SNMP	-	•	
OPC UA	-		
BACnet IP	-		
Profinet	-		

Modularly expandable universal measurement device

UMG 806



Modular expansions for the UMG 806

Modules 806-EC1/ED1/EI1

&





Type	UMG 96-S2		UMG 96RM (UL certified)						
	P	M	E	CBM	EL	PN			
Item number	52.34.002		52.22.061	52.22.064	52.22.069	52.22.062	52.22.066	52.22.068	52.22.090
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	230 / 400 V AC		277 / 480 V AC						
Use in three-phase 3-conductor systems ungrounded up to a max.	-		480 V AC						
Supply voltage	90 – 265 V AC; 90 – 250 V DC		90 – 277 V AC; 90 – 250 V DC ¹						
Three-conductor / four-conductor (L-N, L-L)	- / •		• / •						
Quadrants	4		4						
Sampling rate 50/60 Hz	8 kHz		21.33/25.6 kHz						
National certification according to PTB-A 50.7	-		-						
Effective value from periods (50/60 Hz)	16 / 16		10 / 12						
Residual current inputs	-		- - - 2 - - 2						
Current measuring channels	3		3 4 3 4 4 3 4						
Thermistor input	-		- - - 2 ¹⁴ - - 2 ¹⁴						
Harmonics V / A	1. – 15.		1. – 40.						
Distortion factor THD-U / THD-I in %	•		•						
Unbalance	-		-						
Short-term flicker / long-term flicker	-		-						
Transients	-		-						
Short-term interruptions	-		- - - • - - -						
Accuracy V; A	0.2%; 0.2%		0.2%; 0.2%						
Class A per EN 61000-4-30	-		-						
Active energy class	0.5S (.../5 A)		0.5S (.../5 A)						
Digital inputs	-		- 4 - (3) ⁺³ 4 - (3) ⁺³						
Digital / pulse output	1		2 6 2 (5) ⁺³ 6 - (5) ⁺³ †						
Analogue output	-		-						
Memory min. / max. values	•		•						
Memory size	-		256 MB		256 MB		256 MB		-
Clock	-		- • - • - - -						
Integrated logic	-		Comparator						
Web server / e-mail	-		- - - • / • - - - • / -						
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-		-						
Fault recorder function	-		-						
Peak load optimisation	-		-						
Software for energy management and network analysis	GridVis®-Basic		GridVis®-Basic						
Interfaces									
RS232	-		-						
RS485	•		• • - • • - •						
USB	-		- • - - • - -						
D-Sup-9-connector (Profibus)	-		- • - - - - -						
M-Bus	-		- - • - - - -						
Ethernet	-		- - - • - - • 2						
Protocols									
Modbus RTU	•		• • - • • - •						
Modbus gateway	-		- - - • - - -						
Profibus DP V0	-		- • - - - - -						
Modbus TCP/IP, Modbus RTU over Ethernet	-		- - - • - • •						
SNMP	-		- - - • - - - ⁶						
OPC UA	-		-						
BACnet IP	-		- - - • ² - - -						
Profinet	-		- - - - - •						

UMG 96-S2

Entry-level universal energy measurement device

UMG 96RM

Multifunctional power analyzer



Type	UMG 96-PA (UL certified)			UMG 96-PA modules (UL certified)	
	96-PA	96-PA-MID	96-PA-MID+	96-PA-RCM-EL	96-PA-RCM
Item number	52.32.001 ^{*1}	52.32.003 ^{*8}	52.32.004 ^{*8}	52.32.010	52.32.011
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max.	347 / 600 V AC (acc. to UL) ^{*13} 417 / 720 V AC (acc. to IEC)				
Use in three-phase 3-conductor systems ungrounded up to a max.	-				
Supply voltage	90 – 277 V AC; 90 – 250 V DC ^{*1}				
Three-conductor / four-conductor (L-N, L-L)	- / •				
Quadrants	4				
Sampling rate 50/60 Hz	8.33 kHz				
National certification according to PTB-A 50.7	-	-	•		
Effective value from periods (50/60 Hz)	10 / 12				
Residual current inputs	-			2	
Current measuring channels	3 ^{*7}			1	
Thermistor input	-			1	
Harmonics V / A	1 – 40.				
Distortion factor THD-U / THD-I in %	•				
Unbalance	-				
Short-term flicker / long-term flicker	-				
Transients	-				
Short-term interruptions	-				
Accuracy V; A	0.2%; 0.2%				
Class A per EN 61000-4-30	-				
Active energy class	0.2S (.../5 A)				
Digital inputs	3				
Digital / pulse output	3				
Analogue output	1				
Memory min. / max. values	•				
Memory size	8 MB				
Clock	•				
Integrated logic	Comparator				
Web server / e-mail	-				
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	-				
Fault recorder function	-				
Peak load optimisation	-				
Software for energy management and network analysis	GridVis®-Basic			GridVis®-Basic	
Interfaces					
RS232	-				
RS485	•				
USB	-				
D-Sup-9-connector (Profibus)	-				
M-Bus	-				
Ethernet	-			• -	
Protocols					
Modbus RTU	•				
Modbus gateway	-			• -	
Profibus DP V0	-				
Modbus TCP/IP, Modbus RTU over Ethernet	-			• -	
SNMP	-				
OPC UA	-				
BACnet IP	-				
Profinet	-				

UMG 96-PA

Modularly expandable energy measurement device (MID)

UMG 96-PA modules

Modular expansion for the UMG 96-PA



Type	UMG 509-PRO (UL certified)	UMG 512-PRO (UL certified)
Item number	52.26.001	52.17.011
Use in three-phase 4-conductor systems with grounded neutral conductor up to a max. Use in three-phase 3-conductor systems ungrounded up to a max.	347 / 600 V AC (acc. to UL) 417 / 720 V AC (acc. to IEC) 600 V AC	347 / 600 V AC (acc. to UL) 417 / 720 V AC (acc. to IEC) 600 V AC
Supply voltage	95 – 240 V AC; 80 – 300 V DC*1	95 – 240 V AC; 80 – 300 V DC*1
Three-conductor / four-conductor (L-N, L-L)	•/•	•/•
Quadrants	4	4
Sampling rate 50/60 Hz	20 kHz	25.6 kHz
National certification according to PTB-A 50.7	-	-
Effective value from periods (50/60 Hz)	10 / 12	10 / 12
Residual current inputs	2	2
Current measuring channels	4	4
Thermistor input	1	1
Harmonics V / A	1. – 63.	1. – 63.
Distortion factor THD-U / THD-I in %	•	•
Unbalance	•	•
Short-term flicker / long-term flicker	-	•
Transients	> 50 µs	> 39 µs
Short-term interruptions	•	•
Accuracy V; A	0.1%; 0.2%	0.1%; 0.1%
Class A per EN 61000-4-30	-	•
Active energy class	0.2S (.../5 A)	0.2S (.../5 A)
Digital inputs	2	2
Digital / pulse output	2	2
Analogue output	-	-
Memory min. / max. values	•	•
Memory size	256 MB	256 MB
Clock	•	•
Integrated logic	Jasic® (7 Prg.)	Jasic® (7 Prg.)
Web server / e-mail	•/•	•/•
APPs: Measured value monitor, EN 50160 & IEC 61000-2-4 Watchdog	•	•
Fault recorder function	•	•
Peak load optimisation	-	-
Software for energy management and network analysis	GridVis®-Basic	GridVis®-Basic
Interfaces		
RS232	-	-
RS485	•	•
USB	-	-
D-Sup-9-connector (Profibus)	•	•
M-Bus	-	-
Ethernet	•	•
Protocols		
Modbus RTU	•	•
Modbus gateway	•	•
Profibus DP V0	•	•
Modbus TCP/IP, Modbus RTU over Ethernet	•	•
SNMP	•	•
OPC UA	-	-
BACnet IP	•*2	•*2
Profinet	-	-

UMG 509-PRO

UMG 512-PRO

Certified power quality analyzer (Class A according to IEC 61000-4-30)

Multifunctional power quality analyzer

3-IN-1 MONITORING

One System – three benefits

Benefit from our competence and our extensive services for the whole product life cycle. The hardware and software components are ideally geared to each other. Implement energy management, power quality monitoring and residual current monitoring in only one system environment.

Energy management DIN EN ISO 50001

- Reduces CO₂ emissions
- Reduces energy costs
- Improves energy efficiency

Power quality DIN EN 50160

- Ensures availability
- Reduces downtimes
- Optimises maintenance

Residual current monitoring (RCM)

- Effort reduction of the DGUV V3
- Improves supply reliability
- Rapidly identifies faults
- Improves fire protection

POWER QUALITY SOLUTIONS

Improvement of the power quality

Power quality and supply reliability are extremely important. High sensitivity devices and processes are heavily dependent on a clearly defined power quality. In order to ensure stable processes and adequate power supply despite the increasing number of devices which generate grid distortions, steps must be taken to improve the power quality.

Janitza electronics offers a comprehensive package to improve the power quality:

- Power factor correction in both inductive and capacitive ranges
- Dynamic power factor corrections
- Active and passive harmonics filter

Rapid amortisation through:

- Reduction of reactive power and savings in operational costs
- Reduction of harmonics
- Network symmetry between phases
- Reduction of transients and voltage dips
- Compensation with rapid switching actions
- Reduction of switching spikes

